



10" STAGECOACH SHADE DAMP / WET LOCATION CLASSIC SHAPES

PROJECT: _____
QUANTITY: _____ TYPE: _____



SV1007GV
EG - Evergreen



SV1007GV
TQ - Turquoise



SV1007GV
CH - Charcoal



SV1007GV
OR - Orange

SERIES	LUMENS ¹		CCT	DRIVER / DIMMING ²		ACCESSORIES ⁵		MOUNTING ⁷		FINISH ¹¹		WET KIT			
SV1007GV	15L 27L	1500 Lm 2700 Lm	80 CRI		EX DS10X DO10X ³ DS2W1 DLTE1 ⁴ DL3EX ⁴ Electronic Driver, 120V/277V 10%, 0-10V, 120V/277V 1%, 0-10V, 120V/277V ELV/MLV, 120V Lutron® 2-Wire Forward Phase (MLV), 120V 1%, Lutron® EcoSystem®, Fades to Black, 120V/277V	ENCLOSURES		WALL MOUNT		MW ¹² MB ¹² PT ¹² CC	Matte White Matte Black Platinum Silver Custom Color	WLKA	Wet Location Kit		
			27K 30K 35K 40K	2700K 3000K 3500K 4000K		TF1 ⁶ TG1 MF1 MG1 FJ1 FG1	CP104 CP104KO CP106 CP6/RMD SP90, ⁸ PA, ⁸	Small Driver Canopy Small Driver Canopy w/ Knockouts Large Driver Canopy Remote Mount Driver Straight Arm Mounting Arm Style							
			90 CRI					CEILING MOUNT						See Page 5 for Full Range of Color Options (83-90082)	
			27HK 30HK 35HK 40HK	2700K 3000K 3500K 4000K		RDC5 CP13 HM ⁹ AT ⁹ PM ⁹ CD ⁹ CM ⁹ EMCR ¹⁰ EMRM EMEN	Small Driver Canopy Large Driver Canopy Hang Straight Hang Straight All Thread Rigid Pendant Mount Cord / Cable Mount Cord Mount 10W Large Driver Canopy EM 7W Remote EM 7W Remote with Enclosure								

EXAMPLE: SV1007GV15L35KEXTF1/CP104PA15BZ

NOTES:

1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Available with CP106/RDC5/CP13 Only 4 Available with CP106/CP13 Only
5 Enclosure, Wire Guard Required - Choose One Option 6 Standard Enclosure 7 See Mounting Page for Details on Components and Finishes
8 See Mounting Page for Available Arm Options 9 Specify Length in Inches; See Mounting Page for Available Lengths 10 EMCR Replaces RDC5 or CP13
11 See Color Page for More Options/Consult Factory for Special Finishes 12 Standard Finishes



Spectrum Lighting




10" STAGECOACH SHADE DAMP / WET LOCATION CLASSIC SHAPES

LUMENS / WATTAGE DATA

PART NUMBER	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
SV1007GV15L	1500	1101	10	110
SV1007GV27L	2700	1922	18	107

¹ Nominal Source Lumens at 35K ² Nominal Delivered Lumens at 35K

HOUSING DIMENSIONS



A	B
10.1 256.1 mm	8.0 203.2 mm

APPLICATION

The Stagecoach Shade RLM has a classic bell shape for decorative downlighting.

FEATURES

Spectrum Lighting's RLM Classics are inspired by vintage lighting fixtures redesigned with modern LED light sources and materials. The wide range of options for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. LED module and driver are serviceable for future replacement.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Matte White interior standard.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe and may be field cut.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Wet Location Option. Manufactured and tested to UL standards No. 1598/8750.

ENCLOSURES

TF1

3" FROSTED DOME



MF1

3" FROSTED MINI



FJ1

3" FROSTED TALL



TG1

3" FROSTED DOME
WIRE GUARD - FITS TF1



MG1

3" FROSTED MINI
WIRE GUARD - FITS MF1



FG1

3" FROSTED TALL
WIRE GUARD - FITS FJ1



WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

PA_

MOUNTING ARM STYLE



SV1007GV SHOWN WITH CP104PA23

CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



SV1007GV SHOWN WITH RDC5PM

CD

CORD / CABLE MOUNT



SV1007GV SHOWN WITH RDC5CD

CM

CORD MOUNT



SV1007GV SHOWN WITH RDC5CM



10" STAGECOACH SHADE
DAMP / WET LOCATION
CLASSIC SHAPES / PHOTOMETRIC DATA

SV1007GV-27L-35K-EX-TF1-MWI

CANDLEPOWER CURVE		INTENSITY		ZONAL LUMENS		SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT																
		0.00°		0° - 10°	80	4%																				
		0.00°	842	0° - 20°	301	16%		5.50 ' 28 fc	14.1 ' 10 fc	8' 8' *	23	0.24	19	0.24												
		5.00°	834	0° - 30°	624	32%		6.50 ' 20 fc	16.7 ' 7 fc	12' 10" **	20	0.20	16	0.20												
		10.00°	815	0° - 40°	1,005	52%		7.50 ' 15 fc	19.2 ' 6 fc	16' 12" ***	13	0.14	7	0.09												
		15.00°	784	0° - 60°	1,706	89%		8.50 ' 12 fc	21.8 ' 4 fc	Delivered Illuminance Rating: (DIR)		99 FC per W/Sq. Ft.		79 FC per W/Sq. Ft.												
		20.00°	745	0° - 80°	1,910	99%		10.00 ' 8 fc	25.6 ' 3 fc																	
		30.00°	655	0° - 90°	1,921	100%		12.00 ' 6 fc	30.8 ' 2 fc	<div>2' Suspension Length</div> <div>Square rooms used for multiple units:</div> <div>- RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00</div> <div>- RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50</div> <div>* Average Footcandles at 2.5' Above Floor</div> <div>* Exceeds spacing criteria by 99%</div> <div>** Exceeds spacing criteria by 16%</div> <div>*** Exceeds spacing criteria by -9%</div>																
		40.00°	565	Total	1,921	100%		14.00 ' 4 fc	35.9 ' 2 fc																	
		50.00°	448					16.00 ' 3 fc	41.0 ' 1 fc																	
		60.00°	227																							
		70.00°	82																							
		80.00°	21																							
		90.00°	1																							
Delivered Lumens: 1,921		CP at 0deg (Nadir): 842		Beam Angle: 102.99		Lamp Multiplier: 15L x 0.573																				
Luminaire Watts: 18		CRI: 85+		Spacing Ratio: 1.15		CCT Multiplier: 27K x 0.971, 30K x 0.985, 40K x 1.03																				
LER: 106.72																										


MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




WALL MOUNTING

CP104 - SMALL DRIVER CANOPY (STANDARD)
MAY BE USED AS SPLICE BOX FOR DIRECT FEED
NOT AVAILABLE W/ PA16 & PA16F




CP106 - LARGE DRIVER CANOPY
MAY BE USED AS SPLICE BOX FOR DIRECT FEED



CP6/RMD - REMOTE MOUNT DRIVER
MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX




CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.




CEILING MOUNTING


RDC5 - SMALL DRIVER CANOPY (STANDARD)
MOUNTS TO 4" OCTO J-BOX



CP13 - LARGE DRIVER CANOPY




HM*
HANG STRAIGHT
45° SWIVEL 5/8" OD STEM - 3/8" IP




ORDER: HM (Length)
SPECIFY LENGTH:
HM3 - 3" HM24 - 24"
HM6 - 6" HM36 - 36"
HM12 - 12" HM48 - 48"
HM18 - 18" HM72 - 72"
HMLC(XX)
Custom Length
(Specify in Inches)

PM*
RIGID PENDANT MOUNT
RIGID 5/8" OD STEM - 3/8" IP




ORDER: PM (Length)
SPECIFY LENGTH:
PM3 - 3" PM24 - 24"
PM6 - 6" PM36 - 36"
PM12 - 12" PM48 - 48"
PM18 - 18" PM72 - 72"
PMLC(XX)
Custom Length
(Specify in Inches)

AT**
HANG STRAIGHT ALL THREAD
45° SWIVEL 5/8" OD STEM - 1/4" IP



ORDER: AT (Length)
SPECIFY LENGTH:
AT12 - 12"
AT24 - 24"
AT36 - 36"
AT48 - 48"
AT60 - 60"
AT72 - 72"
FIELD CUTTABLE
FIELD CUT THREADED PIPE TO LENGTH NEEDED
CUT PIPE COVER 1/8" SHORTER
SUPPLY COVER OVER THREADED PIPE

CD
CORD / CABLE MOUNT
SJ CORD WITH 1/16 SS CABLE



ORDER: CD (Length)
SPECIFY LENGTH:
CD36 - 36"
CD72 - 72"
CD144 - 144"
CDLC(XX)
Custom Length
(Specify in Inches)

CM
CORD MOUNT
SJ CORD WITH STRAIN RELIEF




ORDER: CM (Length)
SPECIFY LENGTH:
CM36 - 36"
CM72 - 72"
CM144 - 144"
CMLC(XX)
Custom Length
(Specify in Inches)

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.
**ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT


EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY




REMOTE EMERGENCY BATTERY OPTIONS

EMRM* - 7W REMOTE EMERGENCY BATTERY (50' MAX)



EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)



*OTHER EM BATTERY SIZES AVAILABLE. CONTACT FACTORY.



COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	①
Tier 2 - Typical Finishes	\$\$	①①
Tier 3 - Special Metal Finishes	\$\$\$	①①①
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

TIER 1 - STANDARD FINISHES

MW Matte White	GW Gloss White	PT Platinum Silver	MB Matte Black	GB Gloss Black	BZ Bronze

TIER 2 - TYPICAL FINISHES

TW Textured White	TB Textured Black	MT* Textured Silver	OB* Oil Rubbed Bronze	SN Sun Gold	CO Copper Metallic	BR Brecchia	GH Graphite	CH Charcoal	AL Almond	VE Verde Green
BL Blue Streak	RD Red Baron	OR Orange	CM Carnel	PL Purple	PG Pub Green	TQ Turquoise	SF Sea Foam	PK Pink	AY Aero Yellow	EG Evergreen
LG Lime Green	LB Light Blue	BY Burgundy	AK Anodic Black	AM Anodic Malachite	AZ Anodic Bronze	AS Anodic Sapphire	AN Anodic Natural	AC Anodic Champagne		

TIER 3 - SPECIAL METAL FINISHES

NOT AVAILABLE ON ALL FIXTURES. PLEASE CONSULT SPECIFICATION SHEETS OR FACTORY FOR AVAILABILITY.

GA* Galvanized	BA**/** Brushed Aluminum	GF* Gold Flake

CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION

**UNAVAILABLE FOR INTERIOR

