
8" ROUND REFLECTOR/BAFFLE

PROJECT:		recessed fixtures
QUANTITY:	TYPE:	





7.5

190.5 mm

16.3

412.8 mm

12.0

SG8IN

APPLICATION

Series features a deep reflector for excellent cutoff.

FEATURES

Efficient reflector design optimized for PAR30/PAR38 LED lamps (Sold by others). Posi-lock reflector attachment. Integral 5/8" (0.625") plaster ring. Tool-less access for ease of maintenance. Multi-bar adjustable mounting brackets.

TRIM FINISH

Variety of powdercoat and anodized finishes available on trim.

ELECTRONICS

120V Electronic transformer is standard.

CONSTRUCTION

Frame constructed of 20 ga. galvanized steel. Reflectors spun from .063 high purity aluminum and finished to specification.

CODE COMPLIANCE

ETL listed for damp locations. Manufactured and tested to UL Standard No. 1598.

PRODUCT SELECTOR GUIDE

0.9

235.0 mm



HOUSING			MOUNTING OPTIONS		TRIM OPTIONS					
SERIES		OPTIONS	BAR HANGERS		П	TRIM FINISH		FLANGE FINISH		
SGBIN	CR TR	Corrosion Resistant Top Relamping Option		27" Solid Bars 12" - 24" Expandable Bars 24" C-Channel Bars		AR8115	SG MW MB	Low Iridescent Matte White	MF WF	Matching Flange White Flange For Use with Non-White Trim Finish



