

PROJECT:	
QUANTITY:	TYPE:

A	В
3.9	11.0
99.1 mm	279.4 mm

## SX1003SQLEDGV

### APPLICATION

Cloud 11" surface square light for area illumination.

### **FEATURES**

Speclume series fixtures offer contemporary style with functional luminaire performance. Fixtures designed and manufactured in our factory. Fixture produces horizontal and vertical illumination. Designed for through wiring. Reflective gloss white reflector behind LED for enhanced light output. Interchangeable LED module for ease of maintenance. A variety of mounting options are available.

### **FINISH**

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes.

### **ELECTRONICS**

GV LED system features high brightness white Samsung LED's. 3 step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

### CONSTRUCTION

Fixtures are fabricated in our factory from .063 high purity aluminum. Passive aluminum heatsink for optional thermal management. Formed UV stabilized opal white acrylic diffuser.


BAA Compliant. ETL listed for damp locations. ADA Compliant. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE				
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS	
SX1003SQLEDGV15L	SX1003SQLEDGV14W	1500	9	

SERIES	Ш	JMENS <sup>1</sup>	C	ССТ	DRI	VER / DIMMING <sup>2</sup>	OPTIONS <sup>3</sup>	ı	//OUNTING⁴	DIFFUSER		FINISH <sup>6</sup>
SX1003SQLEDGV	15L	1500 Lm	30K 35K	2700K 3000K 3500K 4000K	D010X	Electronic Driver, 120V/277V 1% 0-10V Dimming, 120V/277V 2 Wire Phase Dimming, 120V	Fuse Holder and Fuse Ceiling Level Gasket	HM_ <sup>5</sup>	Surface Mount Hang Straight Swivel Fitting Pendant Mount Wall Mount	White Opal Acrylic White Opal Polycarbonate	MB <sup>7</sup> PT <sup>7</sup>	Matte White Matte Black Platinum Silver Custom Color
											f	See Page 2 for Full Range of Color Options (83-90081)

## **EXAMPLE: SX1003SQLEDGV15L35KEXSMOPMW**

1 Nominal Source Lumens at 3500K 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 See Mounting Page for Details on Components and Finishes 5 Specify Length in Inches: See Mounting Page for Available Lengths 6 Contact Factory for Special Finishes 7 Standard Finishes





# **COLOR OPTIONS** - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



## STANDARD CORD / STEM / CANOPY FINISHES

	PAI	NT	ΤI	M	ES
1					

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	0
Tier 2 - Typical Finishes	\$\$	00
Custom Color	Contact Factory	Contact Factory

<sup>\*</sup>CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

# **TIER 1 - STANDARD FINISHES**



# **TIER 2 - TYPICAL FINISHES**



# **CUSTOM COLOR FINISHES**

CONTACT FACTORY

CC Custom Color



<sup>\*</sup>UNAVAILABLE FOR WET LOCATION

