




QUADRO 6" CUBE
CLOSED BOTTOM
 DAMP LOCATION
 QUADRO

PROJECT: _____
 QUANTITY: _____ TYPE: _____



CY0608SQCBFAGV
 AL - Almond



CY0608SQCBFAGV
 GB - Gloss Black



CY0608SQCBFAGV
 GW - Gloss White



CY0608SQCBFAGV
 AM - Anodic Malacite

| SERIES | LUMENS ¹ | CCT | DRIVER / DIMMING ² | MOUNTING ³ | FINISH ⁴ |
|----------------|---------------------|-----------|--|---|---|
| CY0608SQCBFAGV | 15L 1500 Lm | 27K 2700K | EX Electronic Driver, 120V/277V DO10X 1% 0-10V, 120V/277V DS2W1 ELV/MLV, 120V | RDC5⁴ Small Driver Canopy HM⁵ Hang Straight AT⁵ Hang Straight All Thread PM⁵ Rigid Pendant Mount CD⁵ Cord / Cable Mount CM⁵ Cord Mount SM Surface Mount EMCR⁷ 10W Canopy Mounted EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure | MW⁶ Matte White MB⁶ Matte Black PT⁶ Platinum Silver CC Custom Color |
| | | 30K 3000K | | | See Page 5 for Full Range of Color Options (83-90081) |
| | | 35K 3500K | | | |
| | | 40K 4000K | | | |
| | | | | | |

EXAMPLE: CY0608SQCBFAGV15L30KEX/RDC5HMPT

NOTES:
 1 Nominal Source Lumens at 40K 2 Contact Factory for Additional Options 3 See Mounting Page for Details on Components and Finishes 4 Required for Driver
 5 Specify Length in Inches: See Mounting Page for Available Lengths 6 Not Available with Surface Mount 7 EMCR Replaces RDC5 8 See Color Page for More Options/Consult
 Factory for Special Finishes 9 Standard Finishes






QUADRO 6" CUBE CLOSED BOTTOM DAMP LOCATION

GV SERIES

| LUMENS / WATTAGE DATA | | |
|-----------------------|----------------------------|--------------|
| PART NUMBER | SOURCE LUMENS ¹ | SYSTEM WATTS |
| CY0608SQCBFAGV15L | 1500 | 11.3 |

¹ Nominal Source Lumens at 35K

HOUSING DIMENSIONS



APPLICATION

Quadro 6" Cube features a clean design for a variety of architectural area lighting. Opal White acrylic shade glows softly and evenly.

FEATURES

Speculume series fixtures offer contemporary style with functional luminaire performance. Fixtures are designed and manufactured in our factory. LED module and drivers are replaceable and upgradable. Electronic LED Driver in canopy for thermal management. A variety of finishes and mounting is available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixtures constructed of spun, machined and formed aluminum and opal white acrylic.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / PM

HANG STRAIGHT / PENDANT



CY0608SQCBFAGV SHOWN WITH RDC5PM

CD

CORD / CABLE MOUNT



CY0608SQCBFAGV SHOWN WITH RDC5CD

CM

CORD MOUNT



CY0608SQCBFAGV SHOWN WITH RDC5CM

SM

SURFACE MOUNT



CY0608SQCBFAGV SHOWN WITH SM





QUADRO 6" CUBE CLOSED BOTTOM DAMP LOCATION

QUADRO / PHOTOMETRIC DATA

DECORATIVE

CY0608SQCBFAGV 27L 35K XX XX MW

| CANDLEPOWER CURVE TEST SP-00987 | INTENSITY CANDELA 0° AZIMUTH | ZONAL LUMENS | SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE | MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT | | | | | | | | | | | | | | | | | | | | | | | | | | |
|------------------------------------|------------------------------------|--------------|--|---|---------------------|------|-------|--|------|-----------|------|-----------|----|----|----|------|----|------|-----|----|----|------|---|------|-----|-----|----|------|---|------|
| | 0° | 0° - 10° | Mounting Height AFF | <table border="1"> <thead> <tr> <th colspan="2">RCR 2</th> <th colspan="2">RCR 4</th> </tr> <tr> <th>FC *</th> <th>W/Sq. Ft.</th> <th>FC *</th> <th>W/Sq. Ft.</th> </tr> </thead> <tbody> <tr> <td>9'</td> <td>6'</td> <td>23</td> <td>0.40</td> <td>17</td> <td>0.40</td> </tr> <tr> <td>12'</td> <td>8'</td> <td>15</td> <td>0.26</td> <td>7</td> <td>0.17</td> </tr> <tr> <td>16'</td> <td>10'</td> <td>10</td> <td>0.18</td> <td>3</td> <td>0.08</td> </tr> </tbody> </table> | RCR 2 | | RCR 4 | | FC * | W/Sq. Ft. | FC * | W/Sq. Ft. | 9' | 6' | 23 | 0.40 | 17 | 0.40 | 12' | 8' | 15 | 0.26 | 7 | 0.17 | 16' | 10' | 10 | 0.18 | 3 | 0.08 |
| | RCR 2 | | RCR 4 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | FC * | W/Sq. Ft. | FC * | W/Sq. Ft. | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 9' | 6' | 23 | 0.40 | 17 | 0.40 | | | | | | | | | | | | | | | | | | | | | | | | |
| | 12' | 8' | 15 | 0.26 | 7 | 0.17 | | | | | | | | | | | | | | | | | | | | | | | | |
| | 16' | 10' | 10 | 0.18 | 3 | 0.08 | | | | | | | | | | | | | | | | | | | | | | | | |
| | 130 | 13 | 1% | 5.5' | 4 fc | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 20° | 0° - 30° | 136 | 9% | 7.5' | 2 fc | | | | | | | | | | | | | | | | | | | | | | | | |
| | 155 | 0° - 60° | 567 | 36% | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 40° | 90° - 120° | 387 | 25% | 10.0' | 1 fc | | | | | | | | | | | | | | | | | | | | | | | | |
| 171 | 90° - 150° | 443 | 28% | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 60° | Downlight | 1,115 | 72% | 12.0' | 1 fc | | | | | | | | | | | | | | | | | | | | | | | | | |
| 168 | Uplight | 444 | 28% | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 80° | Total | 1,558 | 100% | Delivered Illuminance Rating: (DIR) | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 145 | | | 58 FC per W/Sq. Ft. | | 43 FC per W/Sq. Ft. | | | | | | | | | | | | | | | | | | | | | | | | | |
| 90° | | | 1' Suspension Length to luminous height midpoint Square rooms used for multiple units: RCR 2: Length & Width = Ceiling Ht. - 5.5' x 5.00 RCR 4: Length & Width = Ceiling Ht. - 5.5' x 2.50 * Average Footcandles at 2.5' Above Floor | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 131 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100° | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 127 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 120° | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 95 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 140° | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 160° | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 180° | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Delivered Lumens: 1,558
Luminaire Watts: 19
LER: 82.00

CRI: 80+

Beam Angle: 235°
Spacing Ratio: 1.90

Lumen Multiplier: 1.5L x 0.57
CCT Multiplier: 27K x 0.97, 30K x 0.99, 40K x 1.03



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF SPEC LUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



CEILING MOUNTING

| | | | | | |
|--|--|--|--|--|--|
| <p>RDC5 - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p>ORDER: RDC5 (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p> | <p>HM* HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p> | <p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT24 - 24" AT36 - 36" ATLC(XX) Custom Length (Specify in Inches)</p> <p><small>FIELD CUT THE SCOPE TO LENGTH NEEDED. CUT PIPE COVER SLIP SHORTER THAN THREADED PIPE. SLIP PIPE COVER OVER THREADED PIPE.</small></p> | <p>PM* RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMILC(XX) Custom Length (Specify in Inches)</p> | <p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p> | <p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p> |
|--|--|--|--|--|--|

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.

EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY (FOR ROUND CEILING MOUNT TYPES)

REMOTE EMERGENCY BATTERY OPTIONS

| <p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table> | A | B | C | 1.3 | 12.6 | 13.0 | <p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table> | A | B | C | 2.0 | 17.0 | 6.2 |
|---|------|------|---|-----|------|------|---|---|---|---|-----|------|-----|
| A | B | C | | | | | | | | | | | |
| 1.3 | 12.6 | 13.0 | | | | | | | | | | | |
| A | B | C | | | | | | | | | | | |
| 2.0 | 17.0 | 6.2 | | | | | | | | | | | |

*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY



COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES

| FIXTURE COLOR | STANDARD CORD COLOR | STANDARD CANOPY / STEM COLOR |
|--|---------------------|------------------------------|
| Matte White, Textured White | Matte White | Matte White |
| Gloss White | Matte White | Gloss White |
| Matte Black, Gloss Black, Textured Black | Matte Black | Matte Black |
| All Others | Matte Black | Same Color as Fixture |
| Custom Color | Contact Factory | Contact Factory |

PAINT TIMES


| TIER | COST | AVERAGE PAINT TIME* |
|----------------------------|-----------------|---------------------|
| Tier 1 - Standard Finishes | \$ | ⌚ |
| Tier 2 - Typical Finishes | \$\$ | ⌚⌚ |
| Custom Color | Contact Factory | Contact Factory |

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

TIER 1 - STANDARD FINISHES



TIER 2 - TYPICAL FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION

