

PROJECT:	
QUANTITY:	TYPE:







MW - Matte White



MB - Matte Black

SERIES	LUMENS1		LUMENS ¹		LUMENS1		(сст	C	RIVER / DIMMING ²		ACCESSORIES ³		GUARDS	M	OUNTING		FINISH ⁵		WET KIT
TX2XILW		1000 Lm 1300 Lm	30K 35K	2700K 3000K 3500K 4000K		Electronic Driver, 120V/277V 1%, 0-10V, 120V/277V	PJ3 AMJ1 RDJ1 GRJ1	3" Frosted Glass Enclosure 3" Prismatic Lamp Enclosure 3" Amber Lamp Enclosure 3" Red Lamp Enclosure 3" Green Lamp Enclosure 3" Blue Lamp Enclosure	CG1	Cast Wire Guard	CP106	Wall Mount with Driver in J-Box	MB ⁶ PT ⁶ CC	Matte White Matte Black Platinum Silver Custom Color See Page 3 Full Range of color Options	WLKA	Wet Location Kit				

EXAMPLE: WJ1X2XT10L35KD010X/FJ1/CG1/CP106/MW


NOTES:

1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Enclosure, Wire Guard Required - Choose One Option 4 Standard Enclosure 5 See Color Page for More Options/Consult Factory for Special Finishes 6 Standard Finishes












HOUSING DIMENSIONS



Α	В	С	D		
22.7	4.2	8.2	7.5		
576.6 mm	106.7 mm	208.3 mm	190.5 mm		

APPLICATION

The XT Series LED Vapor Tight series with T-fitting for twin fixture mount.

FEATURES

Spectrum Lighting's RLM Classics are reproductions of early American lighting fixtures reimagined with modern LED light sources and materials. The wide range of combinations for lamping, enclosures, and finishes allows for creative fixture specification and design. Frosted lamp enclosure (FJ1) is standard. A variety of colored lamp enclosures are available. LED module and driver are serviceable for future replacement.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

ELECTRONICS


LED system features Xicato LED module with proprietary phosphor technology that converts high brightness blue LEDs into uniform white light. Designed to provide consistent, stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 80 with 90, 95 CRI and VividTM options. Variety of electronic 120v/277v and dimming drivers.

CONSTRUCTION

Fixture is constructed of spun and die-cast heavy gauge aluminum.

CODE COMPLIANCE

BAA Compliant. ETL/UL for damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.



COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR			
Matte White, Textured White	Matte White	Matte White			
Gloss White	Matte White	Gloss White			
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black			
All Others	Matte Black	Same Color as Fixture			
Custom Color	Contact Factory	Contact Factory			

PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	0
Tier 2 - Typical Finishes	\$\$	00
Tier 3 - Special Metal Finishes	\$\$\$	000
Custom Color	Contact Factory	Contact Factory

^{*}CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES


TIER 1 - STANDARD FINISHES

MW	GW	PT	MB	GB	BZ
Matte White	Gloss White	Platinum Silver	Matte Black	Gloss Black	Bronze

TIER 2 - TYPICAL FINISHES



TIER 3 - SPECIAL METAL FINISHES




CUSTOM COLOR FINISHES

CONTACT FACTORY

CC Custom Color

CC



^{*}UNAVAILABLE FOR WET LOCATION