

PROJECT:	
QUANTITY:	TYPE:

# SX1003RDLEDGV

### APPLICATION

Cloud 10" surface light for area illumination.

#### **FEATURES**

Speclume series fixtures offer contemporary style with functional luminaire performance. Fixtures designed and manufactured in our factory. Fixture produces horizontal and vertical illumination. Designed for through wiring. Reflective gloss white reflector behind LED for enhanced light output. Interchangeable LED module for ease of maintenance. A variety of mounting options are available.

### FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes.

### **ELECTRONICS**

GV LED system features high brightness white Samsung LED's. 3 step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

## CONSTRUCTION

Fixtures are spun in our factory from .063 high purity aluminum. Passive aluminum heatsink for optional thermal management. Formed UV stabilized opal white acrylic diffuser.


BAA Compliant. ETL listed for damp locations. ADA Compliant. Manufactured and tested to UL standards No. 1598/8750.


WATTAGE TO LUMENS UPDATE					
CURRENT PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS			
SX1003RDLEDGV15L	SX1003RDLEDGV14W	1500	9		

SERIES	ш	JMENS <sup>1</sup>	C	ССТ	DRIVER / DIMMING <sup>2</sup>		OPTIONS <sup>3</sup>		MOUNTING⁴		DIFFUSER		FINISH <sup>6</sup>	
SX1003RDLEDGV	15L	1500 Lm	30K 35K	2700K 3000K 3500K 4000K	D010X	Electronic Driver, 120V/277V 1% 0-10V Dimming, 120V/277V 2 Wire, MLV Dimming, 120V		Fuse Holder and Fuse Ceiling Level Gasket	HM_ <sup>5</sup> PM_ <sup>5</sup>	Surface Mount Hang Straight Rigid Pendant Wall Mount		White Opal Acrylic White Opal Polycarbonate		Matte White Matte Black Platinum Silver Custom Color
													for C	See Page 2 Full Range of olor Options 83-90082)

## **EXAMPLE:** SX1003RDLEDGV15L35KEXSMOPMW

1 Nominal Source Lumens at 3500K 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 See Mounting Page for Details on Components and Finishes 5 Specify Length in Inches: See Mounting Page for Available Lengths 6 Contact Factory for Special Finishes 7 Standard Finishes





# **COLOR OPTIONS** - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



## STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR		
Matte White, Textured White	Matte White	Matte White		
Gloss White	Matte White	Gloss White		
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black		
All Others	Matte Black	Same Color as Fixture		
Custom Color	Contact Factory	Contact Factory		

## **PAINT TIMES**

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	0
Tier 2 - Typical Finishes	\$\$	00
Tier 3 - Special Metal Finishes	\$\$\$	000
Custom Color	Contact Factory	Contact Factory

<sup>\*</sup>CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

## **TIER 1 - STANDARD FINISHES**

MW	<b>GW</b>	PT	MB	GB	<b>BZ</b>
Matte White	Gloss White	Platinum Silver	Matte Black	Gloss Black	Bronze

# **TIER 2 - TYPICAL FINISHES**



# **TIER 3 - SPECIAL METAL FINISHES**



# **CUSTOM COLOR FINISHES**

CONTACT FACTORY

CC Custom Color



<sup>\*</sup>UNAVAILABLE FOR WET LOCATION



<sup>\*\*</sup>UNAVAILABLE FOR INTERIOR