

## SAFO4PC - TRIM FLANGE / NON IC RATED

### APPLICATIONS

4" square LED adjustable accent light with finished trim flange for Non-IC installations.

### FEATURES

LED module tilts 35°, rotates 360°. Two-stage interchangeable optical and lens systems for smooth light distribution. Zhaga LED module for ease of maintenance and replacement. Shallow plenum design. Tool-less LED module, driver, and J-Box access. Multi-Bar mounting brackets. BH27 Standard aluminum mounting bars included. Posi-lock trim retention torsion springs. Integral 0.625" collar, with plaster option (PR) for up to 3" thick ceiling.

### TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

### ELECTRONICS

LED module features high brightness Philips LEDs. 3-step MacAdam Ellipse binning and 80 and 90 CRI available. Variety of electronic 120V/277V and dimming drivers.


### CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-Flanged one piece trim die cast high purity aluminum and finished to specification.

### CODE COMPLIANCE

BAA Compliant. Non-IC rated. UL listed for damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE			
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS
SAFO4PC10L	SAFO4OC10L	1100	15.2
SAFO4PC20L	SAFO4OC20L	2100	23.5
SAFO4PC30L	SAFO4OC30L	3000	31.0



LED MODULE TILTS AND LOCKS TO 35° AND ROTATES AND LOCKS 360° WHILE MAINTAINING CENTER BEAM FOCUS

SERIES	LUMENS <sup>1</sup>	CCT	OPTICS	DRIVER / VOLTAGE <sup>2</sup>	OPTIONS <sup>3</sup>	TRIM	FINISH	TRIM OPTIONS <sup>8</sup>					
SAFO4PC	80 CRI		ND 20°	E Electronic Driver DS10_ 10%, 0-10V DO10_ 1%, 0-10V	1 120V 2 277V	BH27 <sup>4</sup> 27" Solid Bars H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars EM 7W Emergency Battery Test Switch Remote	SA4FPC <sup>5</sup>	MW <sup>6</sup> Matte White MB Matte Black PT Platinum BZ Bronze CH Charcoal AS Anodic Sapphire AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite CC <sup>7</sup> Custom Color					
	10L 1100 Lm	27K 2700K	MD 30°						SOX <sup>9</sup> Micro Prism Solite™ Lens				
	20L 2100 Lm	30K 3000K	WD 40°						GLX <sup>10</sup> Clear Glass Lens				
	30L 3100 Lm	35K 3500K	XW 50°						PGX Prismatic Glass Lens				
		40K 4000K							FGX Frosted Glass Lens				
	90 CRI												SOW Micro Prism Solite™ Lens
	10L 1000 Lm	27HK 2700K							Wet Location				
	20L 2000 Lm	30HK 3000K							GLW Clear Glass Lens				
									Wet Location				
									PGW Prismatic Glass Lens				
			Wet Location										
			FGW Frosted Glass Lens										
			Wet Location										
			PF <sup>11</sup> Polished Flange										
			AMB Anti Microbial Finish										

**EXAMPLE:** SAFO4PC10L35KMDE1/H12/SA4FPCMWSOX

**NOTES:**  
 1 Nominal Source Lumens at 30K 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard Bar Hangers 5 "F" Indicates Self-Flange Trim, Matte White Standard 6 Standard Finish  
 7 Contact Factory for Special Finishes 8 Contact Factory for Special Lenses / Louvers 9 Standard Lens for MD, WD, XW 10 Standard Lens for ND 11 Flange and Reflector Same Finish



PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.