


HOUSING

# LED MODULE PASSIVE ALUMINUM HEAT SINK OPTICAL SYSTEM WITH LENS NON-FERROUS DIE-CAST ALUMINUM ADJUSTABLE

SELF-FLANGE TRIM

MOUNTING BRACKET



# **6" SQUARE MRI LED DOWNLIGHT**

# OS SERIES / 2000 LUMENS MAX



# **SGE6SQMRILEDOS** - TRIM FLANGE / IC RATED

## APPLICATION

Square OS series LED downlight designed for general illumination. Non-ferrous construction for MRI-Compatible operation.

Two-stage optical system for smooth light distribution. Tool-less LED module, driver, and J-Box access. Multi-Bar mounting brackets. BHMRI Standard aluminum mounting bars included. Posi-lock trim retention torsion springs. Integral 0.625" collar.

A variety of architectural powdercoat and anodized finishes are available. Matte white flange is standard.

## **ELECTRONICS**

LED module features high brightness white Osram LEDs. 3-step MacAdam Ellipse binning and CRI 84 minimum. MRI rated remote 120V/277V 0-10V dimming driver.

### CONSTRUCTION

Housing/frame constructed of non-ferrous material. Self-Flanged one piece trim die-cast high purity aluminum and finished to specification. Extruded and machined 6063-H32 aluminum heatsink. Thermal gasket for optimal thermal management.

## **CODE COMPLIANCE**

BAA Compliant. IC rated. Manufactured and built to UL standards No. 1598/8750.

## INSTALLATION

Remote driver must be mounted beyond the MRI barrier. Power line and control lines must be prepared with EMI/RFI filters (by others).

WATTAGE TO LUMENS UPDATE												
PART NUMBER		SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS									
SGE6SQMRILEDOS10L		1100	12.7									
SGE6SQMRILEDOS15L		1500	17.3									
SGESQ6MRILEDOS20L		2000	22.7									

SERIES	LUMENS <sup>1</sup>			CCT DRIV		ER / LUMENS <sup>1</sup> / DIM		MMING / VOLTAGE <sup>2</sup>			OPTIONS <sup>3</sup>		TRIMS		FINISH	TRIM OPTIONS			
SGE6SQ	10L	1100 Lm	27K	2700K	RMDMRI	Remote	10L	1100 Lm	E_	Electronic	1	120V	BHMRI <sup>4</sup>	27" Aluminum	CA0366OSMRI	MW <sup>6</sup>	Matte White	SO <sup>8</sup>	Micro Prism
MRILEDOS	15L	1500 Lm	30K	3000K		MRI Rated	15L	1500 Lm		Driver	2	277V		Mounting Bars		MB	Matte Black		Solite™ Lens
	20L	2000 Lm	35K	3500K		Driver All	20L	2000 Lm	DS10_	10%, 0-10V			FS	Fusing		SG	Semi-Diffuse	FG	Frosted Glass
			40K	4000K		Drivers			DO10_	1%, 0-10V			PR⁵	Deep Ceiling		HZ	Haze Full Diffuse		Lens
						Remote								Extension		AMB	Anti-Microbial	FO90	White Optical
													EB	Black Housing			Finish		Acrylic
													AMB	Anti-Microbial		CC7	Custom Color	GS	Gasket
														Finish				PF <sup>9</sup>	Polished
																WB	White Micro Baffle		Flange
																ВВ	Black Micro Baffle		

## EXAMPLE: SGE6SQMRILEDOS10L30K/RMDMRI10LDS101/BHMRI/CA0366OSMRIMWSO

1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard Bar Hangers 5 Contact Factory 6 Standard Finish 7 Contact Factory for Special Finishes 8 Standard Lens 9 Flange and Reflector Same Finish



PROJECT: TYPE:







Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.