
# **5" ROUND ADJUSTABLE ACCENT**

PROJECT:		recessed fixtures
QUANTITY:	TYPE:	





5.0

127.0 mm

# SGA5LV

# **APPLICATION**

5" aperture round Low Voltage adjustable accent light.

# **FEATURES**

Efficient reflector design optimized for MR16 LED lamps (sold by others). Wall Wash trim can be rotated, aimed and locked. Integral 5/8" (0.625") plaster ring. Tool-less access for ease of maintenance. Multi-bar adjustable mounting brackets.

#### **TRIM FINISH**

Variety of powdercoat and anodized finishes available on trim.

# **ELECTRONICS**

120V Electronic transformer is standard.

#### CONSTRUCTION

Frame constructed of 20 ga. aluminum. Trim spun from .063" high purity aluminum and finished to specification.

# **CODE COMPLIANCE**

ETL listed for damp locations. Wet location available. Manufactured and tested to UL Standard No. 1598.

# PRODUCT SELECTOR GUIDE

0.6

15.8 mm

8.5 215.9 mm

SERIES	DIMMING	OPTIONS		BAR HANGERS		TRIM	FINISH	FLANGE FINISH	LENS
SGA5LV			/		/	AR5500			
EXAMPLE									
SGA5LV	E1		/	BH27	/	AR5500	SG	MF	SO

16.0

406.4 mm

11.5

292.1 mm

HOUSING			MOUNTING OPTIONS	TRIM OPTIONS		
SERIES	DIMMING	OPTIONS	BAR HANGERS	TRIM FINISH	FLANGE FINISH	LENS
SGASLV	E1 Electronic, 120V	CR Corrosion Resistant TR Top Relamping Option	BH27 H12 27" Solid Bars 12" - 24" Expandable Bars CB24 24" C-Channel Bars	AR5500 SG Semi-Diffuse Low Iridescent MW Matte White MB Matte Black	MF Matching Flange WF White Flange For Use with Non-White Timm Firish	GL Clear Glass Lens SO Micro Prism Solite™ Lens NL No Lens



