



WALLASTON SERIES
DAMP / WET LOCATION
 SUBWAY LINE

PROJECT: _____
 QUANTITY: _____ TYPE: _____



SJ1GV
 RD - Red Baron



SJ1GV
 MB - Matte Black



SJ1GV
 BZ - Bronze



SJ1GV
 AY - Aero Yellow

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	ACCESSORIES ³	MOUNTING ⁴	FINISH ⁷	WET KIT
SJ1GV	15L 27L	1500 Lm 2700 Lm	EX DS10X DS2W1 Electronic Driver, 120V/277V 10%, 0-10V, 120V/277V ELV/MLV, 120V	FJ1⁴ MF1 PJ3 AMJ1 RDJ1 BLJ1 GRJ1 SS1⁵ BS1 CG1 3" Frosted Tall 3" Frosted Mini 3" Prismatic Glass 3" Amber Glass 3" Red Glass 3" Blue Glass 3" Green Glass Side Glass Shield Bottom Shield Cup Cast Guard	CP104 CP104KO Small Driver Canopy Small Driver Canopy w/ Knockouts	MW⁸ MB⁸ PT⁸ CC Matte White Matte Black Platinum Silver Custom Color See Page 4 for Full Range of Color Options (83-90081)	WLKA Wet Location Kit
		80 CRI 27K 2700K 30K 3000K 35K 3500K 40K 4000K 90 CRI 27HK 2700K 30HK 3000K 35HK 3500K 40HK 4000K					

EXAMPLE: SJ1GV15L35KDS10XFJ1CG1/CP104MW

NOTES:

1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Enclosure, Wire Guard Required - Choose One Option 4 Standard Enclosure 5 SS1 Not Available with MFI
 6 See Mounting Page for Details on Components and Finishes 7 See Color Page for More Options/Consult Factory for Special Finishes 8 Standard Finishes






WALLASTON SERIES DAMP / WET LOCATION SUBWAY LINE

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
SJ1GV15L	1500	1027	10	103
SJ1GV27L	2700	1803	18	100

¹ Nominal Source Lumens at 35K ² Nominal Delivered Lumens at 35K

HOUSING DIMENSIONS



Dimensioned with SJ1GV Featuring FJ1 and CG1

A	B
5.5 139.7 mm	11.2 261.6 mm

APPLICATION

The LED Wallaston Series offers rugged design.

FEATURES

Spectrum Lighting's RLM Classics are reproductions of contemporary lighting fixtures reimaged with modern LED light sources and materials. Frosted lamp enclosure (FJ1) is standard. A variety of colored lamp enclosures are available as well as guards and light shields. LED module and driver are serviceable for future replacement.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

ELECTRONICS

GV LED system features high brightness white Samsung LED's, 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.

CONSTRUCTION


Fixture is constructed of die-cast heavy gauge aluminum.

CODE COMPLIANCE


BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Wet Location Option. Manufactured and tested to UL standards No. 1598/8750.

ENCLOSURES


FJ1
3" FROSTED TALL




MF1
3" FROSTED MINI




PJ3
3" PRISMATIC GLASS




AMJ1
3" AMBER GLASS



RDJ1
3" RED GLASS



BLJ1
3" BLUE GLASS




GRJ1
3" GREEN GLASS



SS1
3" SIDE SHIELD



BS1
3" BOTTOM CUP





WALLASTON SERIES


DAMP / WET LOCATION

SUBWAY LINE / PHOTOMETRIC DATA

SJ1GV 27L 35K XX FJ1 MW

CANDLEPOWER CURVE

TEST SP-01054



Delivered Lumens: **1,804**
 Luminaire Watts: **18**
 LER: **100.22**

INTENSITY CANDELA

0° AZIMUTH

Beam Angle	Intensity (cd)
0.00°	402
20.00°	315
40.00°	339
60.00°	264
80.00°	137
90.00°	99
100.00°	75
110.00°	57
120.00°	44
140.00°	11
160.00°	1
180.00°	1

CP at 0deg (Nadir): **402**
 CRI: **80**

SINGLE UNIT: PERFORMANCE

INITIAL FOOTCANDLES
 BASED ON IES BEAM ANGLE

Mounting Height AFF	FC at Center on Floor
6.5'	10 fc
7.5'	7 fc
8.5'	6 fc
10.0'	4 fc
12.0'	3 fc
14.0'	2 fc
16.0'	2 fc
20.0'	1 fc

MULTIPLE UNITS: PERFORMANCE

80/50/20% REFLECTANCES
 INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT

Ceiling Height	Fixture Spacing	RCR 2		RCR 4	
		FC +	W/Sq. Ft.	FC +	W/Sq. Ft.
9'	6'	48	0.60	23	0.38
12'	8'	20	0.25	10	0.16
16'	10'	13	0.17	10	0.17
Delivered Illuminance Rating: (DIR)		80 FC per W/Sq. Ft.		61 FC per W/Sq. Ft.	
1' Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. -3.5' x 5.00 - RCR 4: Length & Width = Ceiling Ht. -3.5' x 2.50 + Average Footcandles at 2.5' Above Floor					

Lumen Multiplier: 15L x 0.573
 CCT Multiplier: 27K x 0.97, 30K x 0.99, 40K x 1.03



COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

PAINT TIMES


TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	⓪
Tier 2 - Typical Finishes	\$\$	⓪⓪
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

TIER 1 - STANDARD FINISHES



TIER 2 - TYPICAL FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION

