

4" -14" ROUND DOWNLIGHT

REMODEL SERIES

Spectrum's A Spec 4"-14" remodel round kelvin and color tuning downlight series features a shallow plenum housing for general illumination.

LUMENS AND WATTAGE CHART								
PART NUMBER		SOURCE LUMENS ¹	SYSTEM WATTS					
SGRTE6LU14L		1400	32					

1 Peak Source Lumens

QUANTITY: TYPE: MATTE WHITE MATCHING FLANGE MATTE BLACK SEMI-DIFFUSE PLATINUM SILVER BRONZE MATCHING FLANGE MATCHING FLANGE MATCHING FLANGE MATCHING FLANGE

PROJECT:

AVAILABLE HOUSING TYPES

SGRTE-LU - DOWLIGHT





PRODUC	T SEL	ECTOR	GUID	E						
		HOUSING						TRIM OPTIONS		
SERIES	LUMENS	CCT / K	BEAM	CONTROL / VOLTAGE		TRIM TYPE	FINISH	FLANGE FINISH	LENS	TRIM OPTIONS
	14L	80СМХ		DMXLU1	/					
EXAMPLE										
SGRTE6LU	14L	80СМХ	MD	DMXLU1	/	AR6223LU	MW	MF	SO	

HOUSING									
SERIES	LUMEN	NS ¹ C	CT / K	BE	AM		CONTROL / VOLTAGE		
SGRTEALU SGRTESLU SGRTESLU SGRTEFILU SGRTEBLU SGRTEBLU SGRTEOLU SGRTEIOLU SGRTEILU SGRTEILU	14L 1400		X 16K-80K	ND MD WD XW	20° 30° 40° 50°	The Hiv	DMX Configuration Unit Control Via Bikinooth ne Antenna. DMX System ad For Multi-Unit System	1 2	

TRIM OPTIONS								
TRIM TYPE		FINISH		FLANGE FINISH		LENS	TI	RIM OPTIONS
AR4466LU AR5466LU	MW MB		MF	Matching Flange NON MATCHING	so	Micro Prism Solite™ Lens	W	Wet Location Gasket Is Supplied
AR6466LU	SG	Semi-Diffuse	WF	White Flange				with "W" Option
AR7466LU AR8466LU	PT CC*		BF SF	Black Flange Platinum Flange			GS	Gasket
AR9466LU AR1066LU		*Consult Factory	CCF*	Custom Color Flange *Consult Factory				
AR1266LU AR1466LU	See Pa	ige (x) for Full Range of	See	Page (x) for Full Range of				
		or Options (83-90178)		color Options (83-90178)				

- Kelvin (16K-80K) and color (RGBW) tuning fixture.
- · True saturated greens, blues and reds.
- Controlable with DMX or Bluetooth controls.
- Peak of 1400 source lumens.
- · Smooth light distribution for general illumination.
- · Shallow plenum construction.
- L70 at >60,000 Hours at 70% lumens maintenance.
- 5 year warranty on fixture and electronics.
- Sustainable fixture.
- Dry/damp or wet location rated.
- · Ease of maintenance.
- Posi-lock trim retention torsion springs.












HOUSING DIMENSIONS

SGRTE-LU - 4"-14" REMODEL CONSTRUCTION / 14L MAX

Non-IC rated frame-in kit for existing construction. Non-IC designation requires insulation must be minimum of 3" from housing.



FIT SIZE									
SERIES	4"	5"	6"	7"	8"	9"	10"	12"	14"
MINIMUM	45/8	51/8	61/8	615/16	73/4	811/16	911/16	1111/16	1311/16
MAXIMUM	47/8	55/8	67/16	77/16	87/16	97/16	109/16	127/16	141/2

SERIES	Α	В	С	D
SGRTE4LU	4.0	5.4	5.5	4.6
SGRTE5LU	5.0	6.3	6.0	5.1
SGRTE6LU	6.0	7.5	6.8	6.2
SGRTE7LU	7.0	8.4	6.8	6.9
SGRTE8LU	8.0	9.1	6.8	7.7
SGRTE9LU	9.0	10.1	6.8	8.6
SGRTE10LU	10.0	11.3	6.8	9.7
SGRTE12LU	12.0	13.1	6.8	11.6
SGRTE14LU	14.0	15.2	7.0	13.8

TRIM DATA

AR6223LU - DOWNLIGHT





FEATURES

APPLICATIONS

4"-14" Round LU downlight retrofit or remodel platform with Tunable color (HUE) system. System can be programmed for scenes or set for manual control. Adjusts to over 300,000 colors as well as 1650K-8000K white light.

FEATURES

Remodel round downlight housing designed for install in finished "hard" ceiling or into existing precut hole. Ouick mount remodel spring clips with mechanical lock down. Return edge to seat fixture in ceiling. Integral 5/8" (.625) collar, works in ceiling up to 1" Deep. Two-stage optical system for smooth light distribution and focus control. Quick change LED module with interchangeable optics for job site adjustment and fixture maintenance. Shallow plenum design. Tool-less driver and j-box access. Posi-lock trim retention torsion springs.

REMODE

Features tethered power supply and junction box with sheathed wire.

FINISH

Variety of powdercoat and anodized finishes available. Matte white flange is standard.

ELECTRONICS

LED system features LED module with proprietary Tunable color (HUE) technology that provides consistent, stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 90 with <2 MacAdam Ellipse binning. Variety of dimming controls (by Others). The Hive Antenna is the main control app., and is available for both Apple and Android devices.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.





SPUN TRIM AND FLANGE FINISH OPTIONS - RECESSED ROUND

SPECTRUM LIGHTING RUNS A STATE OF THE ART POWDER COAT PROCESS WITH A FIVE STAGE CHROMATE PRETREAT AND MULTI STAGE OVEN. THREE BOOTHS ARE FED SO WE ARE ABLE TO RUN MULTIPLE COLORS ON ANY GIVEN DAY, SPECTRUM ALSO HAS A CUSTOM "WET" BOOTH FOR SPECIAL AIR-DRY FINISHES AND PAINTS.



PAINT TIMES

TIER	COST	PAINT TIME*
Tier 1 - Standard Finishes	\$	()
Tier 2 - Typical Finishes	\$	00
Tier 3 - Anodic Finishes	\$\$	00
Tier 4 - Alzak Finishes	\$\$\$	000
Custom Color	Contact Factory	Contact Factory

^{*}CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

FLANGE OPTIONS

WF White Flange



FOR USE WITH NON-MATTE WHITE TRIM FINISH

MF Matching Flange




FOR USE WITH NON-MATTE BLACK TRIM FINISH





FOR USE WITH NON-PLATINUM TRIM FINISH

CCF* Custom Color Flange



POWDER COAT PAINT FINISHES

TIER 1

MW



ΜВ Matte Black





SG**



TIER 2

SN Sun Gold



BZ Bronze



OB Oil Rubbed Bronze



CH Charcoal



CO Copper Metallic



GH Graphite



TIER 3

AS Anodic Sapphire



ΑN Anodic Natural



AC Anodic Champagne



AZ Anodic Bronze



AΜ Anodic Malachite



AK Anodic Black



ANODIZED ALZAK FINISHES

TIER 4

CL Bright Clear



HZ Haze Full Diffuse



WE


GO Gold Alzak Semi-Diffuse



PW Pewter Semi-Diffuse



CC*
Custom Color





AMB*** Anti Microbial





