


1' X 4' PANEL LIGHT DAMP LOCATION PANELUME

PROJECT:

TYPE:



Α	В	С
47.8	11.9	1.9
1213.0 mm	303.0 mm	47.0 mm

APPLICATION

Flat panel 1×4, 2×2, 2×4 series for grid ceiling installation and for general illumination.

ELECTRONICS

Switchable Multi Lumen (2500-6400) and Multi Kelvin (30K-65K) LED system simplifies ordering. 0-10V 1% dimming driver for control of light level. Emergency Battery optional.

CONSTRUCTION

Powder coated aluminum housing with diffuse white acrylic lens.

MOUNTING

Grid ceiling.

FINISH

Matte white powder coat.

	MULTI LUMEN	MULTI KELVIN				
WATTS	DELIVERED LUMENS	CCT				
20W	2500Lm	30K	3000K			
25W	3200Lm	35K	3500K			
30W	3850Lm	40K	4000K			
35W	4480Lm	50K	5000K			
40W	5120Lm	65K	6500K			
50W	6400Lm					

SERIES	LUMENS		ССТ		DRIVER / VOLTAGE		FINISH		EM OPTIONS	
FP14	ML	Multi Lumen	мк	Multi Kelvin	DX	1%, 0-10V, 120V/277V		Matte White Custom Color		Emergency Battery Pack

SPECLIGHT.COM · 994 JEFFERSON ST. FALL RIVER, MA 02721 · 508.678.2303

EXAMPLE: FP14MLMKDXMW



ILLUMINATING WHAT'S POSSIBLE.

Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.