



A	B	C	D	E	F
8.5	0.6	6.0	11.5	16.0	11.5
215.9 mm	15.8 mm	152.4 mm	292.1 mm	406.4 mm	292.1 mm

## 6" SQ. ADJUSTABLE ACCENT R30/ PAR30L/ PAR38 LAMP

150 WATT MAX INCANDESCENT



### SGA6SQIN

#### APPLICATION

6" square PAR30/ PAR38 accent light for incandescent lamps.

#### FEATURES

Efficient trim design with a variety of lens options.

Trim rotates/ locks 360°. Lamp tilts/ locks 35°.

Integral 5/8" (0.625) plaster ring.

Maximum wattage label (MWL) for low wattage Incandescent or LED lamps.

Tool-less ballast access.

Multi-bar adjustable mounting brackets.

#### FINISH

Variety of powdercoat and anodized finishes available on trim.

Eco Black (EB) finish available on frame/ housing.

#### ELECTRONICS

120 Volt is standard. Use option T277 for 277V supply feed.

#### CONSTRUCTION

Frame constructed of 20 ga. aluminum.

Trim formed from .050 high purity aluminum and finished to specification.

#### LABELS

UL/ ETL Listed for Damp locations. Wet location available.

Manufactured and tested to UL Standard No. 1598.

Max Ceiling Thickness:	1.0 (25.4 mm)
Ceiling Cutout:	7.0 <sup>2</sup> (177.8 mm) <sup>2</sup>
Fixture Weight:	6.0 lbs

SERIES	OPTIONS	TRIM / FINISH	TRIM OPTIONS	FIXTURE LAMPING*								
<b>SGA6SQIN-</b> Spectrum Gold 6" Square Adjustable	<b>BH27</b> -27" Bar Hangers (Supplied) <b>CB24</b> -C-Channel Bars <b>CCEA</b> -Chicago Ceiling Plenum <b>CR</b> -Corrosion Resistant <b>T277</b> -Step Down Transformer 277v to 120v <b>FS</b> -Fuse Holder and Fuse <b>PW</b> -Plaster Ring (Special Depth) <b>MWL</b> -Max Wattage Label (Specify Wattage) <b>EB</b> -Eco Black Housing Finish	<b>AR0306-SG</b> -Semi-Diffuse Low-Iridescence (Standard) <b>GM</b> -Corrugated Soft Glow <b>GO</b> -Gold Alzak <b>MB</b> -Matte Black <b>MW</b> -Matte White <b>PW</b> -Pewter Alzak <b>UM</b> -Umber Alzak <b>WE</b> -Wheat Alzak <b>BF</b> -Black Flange <b>WF</b> -White Flange <b>CC</b> -Custom Color	<b>GL</b> -Clear Glass Lens <b>GS</b> -Gasket <b>PG</b> -Prismatic (T73) Lens <b>SO</b> -Micro Prism Solite™ Lens <b>SK</b> -Skytek™ Linear Lens <b>LN</b> -See Recessed Fixtures/ Lens Options for Lens, Louver and Filter Accessories <b>WL</b> -Wet Location	<table border="1"> <thead> <tr> <th>LAMP</th> <th>MAX. WATTAGE</th> </tr> </thead> <tbody> <tr> <td>R30</td> <td>100w</td> </tr> <tr> <td>PAR30L</td> <td>75w</td> </tr> <tr> <td>PAR38</td> <td>150w</td> </tr> </tbody> </table> <p>*Medium Base</p>	LAMP	MAX. WATTAGE	R30	100w	PAR30L	75w	PAR38	150w
LAMP	MAX. WATTAGE											
R30	100w											
PAR30L	75w											
PAR38	150w											

Note: Polished Flange is Standard.

#### EXAMPLE: SGA6SQIN/ AR0306 SG GL

Dimensions shown are nominal. Spectrum Lighting is continually improving products and reserves the right to make changes that will not alter performance or appearance with or without written notice.



PROJECT:	TYPE:
CAT. NO.:	

