



4" ROUND RETROFIT WALL WASH OS SERIES / 4500 LUMENS MAX

retrofits
remodelights



A	B	C
4.0 101.6 mm	5.4 137.2 mm	6.2 157.5 mm

Ceiling Cutout: Ø 4 5/8"

SGRTW4LEDOS - TRIM FLANGE / NON-IC RATED

APPLICATION

Round OS general illumination series LED wall wash for retrofit or remodel applications.

FEATURES

One piece spun housing seals ceiling aperture preventing light leaks. Two-stage optical system for smooth light distribution. Zhaga International Standard LED module for ease of maintenance and replacement. Tool-less LED module, driver, and J-Box access. Posi-lock trim retention torsion springs. Includes set of three retrofit clips to accommodate most installations. Goof ring available for oversized or damaged ceiling installations. Fixture will work in up to 1" thick ceiling¹.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

ELECTRONICS

LED module features high brightness white Osram LEDs. 3-step MacAdam Ellipse binning and CRI 84 minimum. Full range of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Housing/frame constructed of .060 aluminum and powdercoat white to resist corrosion. Self-flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification. Passive machined aluminum heatsink.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL listed for damp locations. Optional Wet location. LM79/LM80/TM21 data available. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE					
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
SGRTW4LEDOS10L	SGRTW4LEDOS14W	1100	643	11	58
SGRTW4LEDOS15L	N/A	1500	793	13	61
SGRTW4LEDOS20L	SGRTW4LEDOS25W	2000	1365	20	68
SGRTW4LEDOS30L	SGRTW4LEDOS35W	3000	1876	28	67
SGRTW4LEDOS45L	N/A	4500	2777	41	68

SERIES	LUMENS ²	CCT	DRIVER / VOLTAGE ³	OPTIONS ⁴	TRIM	FINISH	TRIM OPTIONS
SGRTW4LEDOS	10L 1100 Lm	27K 2700K	E Electronic Driver DS10_ 10%, 0-10V DO10_ 1%, 0-10V DS2W1 1%, ELV/MLV, 120V DLTE1 1% Lutron® 2-Wire Forward Phase, 120V DL3E_ 1% Lutron® EcoSystem®, Fade EL10_ 1%, eldoLED ED01_ 0.1%, eldoLED DALI_ DALI Control	1 120V 2 277V FS Fusing CR Corrosion Resistant GR Goof Ring WP12 12" Whip WP24 24" Whip WP36 36" Whip ZIG ⁵ ZigBee Module BLU ⁶ Bluetooth LE EM ⁶ 7W Emergency Battery Test Switch Remote AMB Anti-Microbial Finish	AR4923OS	MW ⁷ Matte White MB Matte Black SG Semi-Diffuse PT Platinum Silver BZ Bronze OB Oil Rubbed Bronze CH Charcoal AS Anodic Sapphire AN Anodic Natural AC Anodic Champagne AM Anodic Malachite CO Copper Metallic GH Graphite CC ⁸ Custom Color	SK ⁹ Skytex™ Lens GS Gasket WL Wet Location PF ¹⁰ Polished Flange AMB Anti-Microbial Finish
	15L 1500 Lm	30K 3000K					
	20L 2000 Lm	35K 3500K					
	30L 3000 Lm	40K 4000K					
	45L 4500 Lm						

EXAMPLE: SGRTW4LEDOS20L35KE1/AR4923OSMWSK

NOTES:
 1 Consult Factory for Thicker Ceiling 2 Nominal Source Lumens at 35K 3 Contact Factory for Additional Options 4 See Product Options Page for Details 5 Order DS101/2 When Specifying ZIG or BLU 6 Standard EM
 7 Standard Finish 8 Contact Factory for Special Colors 9 Standard Lens 10 Flange and Reflector Same Finish



PROJECT: _____
TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.