





# SIGN LIGHT



## XT SERIES / 1000 LUMENS MAX LED

### SL0306LEDXT

#### **APPLICATION**

3" diameter machined aluminum Sign Light for focused adjustable spot lighting. **FEATURES** 

The wide range of combinations for illumination, mounting and finishes allows for creative fixture specification and design. Fixtures may be wall mounted with standard or custom wall arm (goosenecks). LED module and driver are serviceable for future replacement.

#### **FINISH**

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

#### **ELECTRONICS**

LED system features Xicato LED module with proprietary phosphor technology that converts high brightness blue LEDs into uniform white light. Designed to provide consistent, stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 82 with 90, 95 CRI and VividTM options. Variety of electronic 120v/277v and dimming drivers.

#### CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall enclosures and fittings are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe. Gaskets are machine cut neoprene.

#### CODE COMPLIANCE

ARRA Compliant. ETL listed for damp locations. Optional Wet location. Manufactured and built to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE										
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS							
SL0306LEDXT 10L	SL0306LEDXT 7W	1000	11.1							

SERIES	LUI	MENS <sup>1</sup>	C	ССТ	BE	ΑM	D	RIVER / VOLTAG	ЭE²	2		MOUNTING <sup>3</sup>		FINISH <sup>4</sup>
SL0306LEDXT	10L	1000 Lm	27K	2700° K	ND	20°	E_	Electronic Driver	1	120v	CP104	Wall Driver Housing	GW	Gloss White
			30K	3000° K	MD	30°	DS10_	0-10v Dimming,	2	277v	CP6/RMD	Remote Mount Driver	GB	Gloss Black
			35K	3500° K	WD	40°		to 10%			PA(xx)	See RLM Mounting Page	BZ	Bronze
			40K	4000° K								for Available Arm Options	ОВ	Oil Rubbed Bronze
													PT	Platinum
											WL	Wet Location	SI	Silver
													GA	Galvanized
													CH	Charcoal
													GH	Graphite
													AM	Anodic Malachite
													SN	Sun Gold
													EG	Evergreen
													VE	Verde Green
													BL	Blue Streak
													RD	Red Baron
														Orange
													co	Copper Metallic

**EXAMPLE:** SL0306LEDXT10L30KMDE1/PA23/CP106/WLGW

NOTES:

1 Nominal Source Lumens at Any CCT 2 Contact Factory for Additional Options 3 See Mounting Page for Details 4 Contact Factory for Special Finishes



XICATO



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.



PROJECT: TYPE: CAT. NO.: