SPIKE SCONCE

MR16 SERIES / 50 WATT MAX INC

PROJECT: QUANTITY:

TYPE:

FRMC0314UDINC

APPLICATION

Spike Sconce for decorative wall accent lighting.

FEATURES

Speclume series fixtures offers contemporary style with functional luminaire performance. All fixtures are designed and manufactured in our factory. Spike wall sconce sits flat against wall and projects "Hot" light pattern against wall for dramatic effect. A variety of lens, wattage and other options available. FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

ELECTRONICS

50 watt max MR16. 120 volt standard (E1). 277 volt optional (E2).

CONSTRUCTION

Fixtures are fabricated in our factory from aluminum extrusion.

CODE COMPLIANCE

BAA Compliant. ETL listed for damp locations. Manufactured and tested to UL standards No. 1598.



Detail: Key slots engage hardware at wall box. KO for Power Feed

SERIES	LAMPS	BALLAST		FINISH⁴
FRMC0314UDINC	2 x MR16	El Electronic, 120v	SMF ² Surface Mount Flush	MW Matte White
	50W Max	E2 Electronic, 277v	1.51.0	MB Matte Black
		E1LED Electronic 20W 12v LED	LENS	GW Gloss White
		Rated Transformer	LN16 ³ Lens	GB Gloss Black
		MWL Label with Max Wattage	HL16 Hex Louver	BZ Bronze
				OB Oil Rubbed Bronze
				PT Platinum
				SI Silver
				CH Charcoal
				GH Graphite
				AM Anodic Malachite
				SN Sun Gold
				BL Blue Streak
				RD Red Baron
				CO Copper Metallic
				CC Custom Color

EXAMPLE: FRMC0314UDINC 2XMR16E1/SMF SN

NOTES: 1 Specify Length in Inches 2 Integral Keyslots 3 See Lens Pages 4 Contact Factory for Special Finishes




ILLUMINATING WHAT'S POSSIBLE.

SPECLIGHT.COM • 994 JEFFERSON ST. FALL RIVER, MA 02721 • 508.678.2303

Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.

2022 RA



14.0 3.5 O.C. 3.0 SQ 355.6 mm 88.9 mm 76.2 mm

COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.

STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR	TIER	COST	AVERAGE PAINT TIME*
Matte White, Textured White	Matte White	Matte White	Tier 1 - Standard Finishes	\$	Ū
Gloss White	Matte White	Gloss White	Tier 2 - Typical Finishes	\$\$	00
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black	Tier 3 - Special Metal Finishes	\$\$\$	000
All Others	Matte Black	Same Color as Fixture	Custom Color	Contact Factory	Contact Factory
Custom Color	Contact Factory	Contact Factory	*CONTACT FACTORY FOR SPECIFIC P	RODUCT LEAD TIMES	

PAINT TIMES


TIER 1 - STANDARD FINISHES



TIER 2 - TYPICAL FINISHES



TIER 3 - SPECIAL METAL FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY



*UNAVAILABLE FOR WET LOCATION





SPECTRUM

ILLUMINATING WHAT'S POSSIBLE.