





С

152.4 mm

В

3.5 88.9 mm

4" RECESSED LV REMODELER

MR16 SERIES / 37 WATT MAX LOW VOLTAGE



SGRM4LV - TRIM FLANGE / NON-IC RATED

APPLICATION

4" round architectural remodel Low Voltage MR16 fixture for accent and general illumination.

FEATURES

Designed for remodel installations. Tool-less transformer access. Lamp rotates 360°. Adjustable trim has 30° tilt. One piece-self-flanged trim. Goof ring available for oversized or damaged ceiling installations. Posi-lock trim retention torsion springs. Designed for 0.5" - 1" thick ceilings. Contact factory for ceiling applications (over 1"). Trim matches SGDG4X and SGAG4X series.

A variety of architectural powdercoat and anodized finishes available on reflector/ trim. Flange finished in Matte White standard. Polished flange option (flange finished same as inside).

FLECTRONICS

Electronic 120V transformer is standard. 277V electronic, 120 or 277V magnetic, 120V LED rated electronic and remote transformer options. High temperature rated porcelain GU10 socket.

CONSTRUCTION

Housing/frame constructed of .060 aluminum to resist corrosion. Self flanged one piece trim spun from 0.060" thick high purity aluminum and finished to specification.

Goof rings available for rough or OB-Round holes. Integral retrofit quick mount clips. Optional clips, springs and extended whips available (See options and installation details).

CODE COMPLIANCE

BAA Compliant. ETL Listed for Damp locations. Manufactured and tested to UL standard No. 1598.

FIXTURE LAMPING								
LAMP	MAX WATT							
MR16	37W							







SERIES	TRANSFORMER		OPTIONS		П	TRIM	FINISH		TRIM OPTIONS	
					П					
SGRM4LV	E1	Electronic, 120v	CR	Corrosion Resistant	П	AR4150	SG ³	Semi-Diffuse	GL	Clear Glass Lens
Gold 4" Low Voltage	E2	Electronic, 277v	FS	Fusing	Ш	4" Shallow Downlight Trim	MW	Matte White	so	Micro Prism Solite™ Lens
Retrofit Housing	MGN1	Magnetic Transformer, 120v	MWL(**)1	Maximum Wattage	Ш		MB	Matte Black	PG	Prismatic (T73) Lens
	MGN2	Magnetic Transformer, 277v		Dedicated Transformer	Ш	AR4250	PT	Platinum Silver		
	E1LED	Transformer for Use with LED MR16		and Label	Ш	4" Deep Downlight Trim	PF ⁴	Polished Flange		
		Lamps 120V	RTT150E1	150W Remote Transformer	Ш					
	NTR	No Transformer for Remote	RTT300E1	300W Remote Transformer	Ш	AR4203SA				
		Transformer Application	WP24	24" Whip	Ш	4" Adjustable Trim				
	GU10	GU10 120V Socket No Transformer	WP48	48" Whip	Ш					

EXAMPLE: SGRM4LVMGN1MWL37W/AR4203SASGGS

Α

114.3 mm

NOTES:
1 20W, 37W, 50W 2 Contact Factory for Special Finishes 3 Standard Finish 4 Flange and Reflector Same Finish 5 Contact Factory for Special Lenses/Louvers

101.6 mm



PROJECT: TYPE:



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.