





MACHINED ALUMINUM MULTI-BAR TRIM FOR PRECISE FIT MOUNTING BRACKET





4" TECHZONE™ DOWNLIGHT OS SERIES / 4500 LUMENS MAX

recessed fixtures

SGTZ4LEDOS - TECHZONE™ / NON-IC RATED

APPLICATION

4" Square Recessed downlight series for installation in TechZone™ 4" ceilings. **FEATURES**

Two-stage optical system for smooth light distribution. Zhaga International Standard LED module for ease of maintenance and replacement. Tool-less LED module, driver and J-Box access.

FINISH

Trim is powdercoated Matte White.

ELECTRONICS

LED module features high brightness white Osram LEDs. 3-step MacAdam Ellipse binning and CRI 84 minimum. Full range of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Flangeless one piece trim extruded high purity aluminum and finished.


CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

INSTALLATION

TechZone™ base fixture fits 15/16 T-Bar flat or tegular tile. Optional 9/16 T-Bar or tegular tile.

| WATTAGE / LUMENS DATA | | | | | | | | | | |
|-----------------------|-------------------------------|-----------------|--|--|--|--|--|--|--|--|
| PART NUMBER | SOURCE LUMENS ¹ | SYSTEM WATTS | | | | | | | | |
| SGTZ4LEDOS10L | 1100 | 11 | | | | | | | | |
| SGTZ4LEDOS15L | 1500 | 13 | | | | | | | | |
| SGTZ4LEDOS20L | 2000 | 20 | | | | | | | | |
| SGTZ4LEDOS30L | 3000 | 28 | | | | | | | | |
| SGTZ4LEDOS45L | 4500 | 41 | | | | | | | | |



Shown with T-Bar

| SERIES | SERIES LUMENS ¹ | | CCT | | DRIVER / DIMMING / VOLTAGE ² | | | OPTIONS ³ | | TRIM OPTIONS ⁶ | | |
|------------|----------------------------|---|------------|----------------------------------|---|--|--|----------------------|----------------------------------|--|--|---|
| SGTZ4LEDOS | 15L 20L 30L | 1100 Lm 1500 Lm 2000 Lm 3000 Lm 4500 Lm | 30K 35K | 2700K 3000K 3500K 4000K | DS10_ DO10_ DS2W1 DLTE1 DL3E_ EL10_ ED01_ | Electronic Driver 10%, 0-10V 1%, 0-10V 1%, ELV/MLV, 120V 1% Lutron® 2-Wire Forward Phase, 120V 1% Lutron® EcoSystem®, Fade 1%, eldoLED 0.1%, eldoLED DALI Control | | 120V 277V | EM⁴ CR ZIG⁵ BLU⁵ 916 | Fusing 7W Emergency Battery Test Switch Remote Corrosion Resistant ZigBee Module Bluetooth LE 9/16 T-Bar Anti- Microbial Finish | | Matte White Acrylic Lens Anti-Microbial Finish |

EXAMPLE: SGTZ4LEDOS20L30KE1MWFO90

NOTES:

1 Norminal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard EM 5 Order DS101/2 When Specifying ZiG or BLU 6 Matte White Trim Supplied 7 Standard Lens



PROJECT: TYPE:



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.