

MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF LUMEN MAX SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



MOUNTING TYPES

| | | | |
|--|---|---|---|
| <p>HM* HANG STRAIGHT 45° SWIVEL 5/8" OD STEM - 3/8" IP</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p> | <p>PM* RIGID PENDANT MOUNT RIGID 5/8" OD STEM - 3/8" IP</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLC(XX) Custom Length (Specify in Inches)</p> | <p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p> | <p>HC HOOK & CORD FOR INDEPENDENT MOUNTING</p> <p>ORDER: HC</p> |
|--|---|---|---|

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36".
LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.

EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY

REMOTE EMERGENCY BATTERY OPTIONS

| <p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50" MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table> | A | B | C | 1.3 | 12.6 | 13.0 | <p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50" MAX)</p> <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table> | A | B | C | 2.0 | 17.0 | 6.2 |
|---|------|------|---|-----|------|------|---|---|---|---|-----|------|-----|
| A | B | C | | | | | | | | | | | |
| 1.3 | 12.6 | 13.0 | | | | | | | | | | | |
| A | B | C | | | | | | | | | | | |
| 2.0 | 17.0 | 6.2 | | | | | | | | | | | |

*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY

ADDITIONS

| | |
|--|--|
| <p>FS - FUSING</p> <p>Slow blow type fuse protects fixture against voltage surges. Factory installed.</p> | <p>FCMA - FIELD CUTTABLE MOUNTING KIT FOR HANG MOUNT FIXTURES</p> |
|--|--|

SAFETY CABLE OPTIONS

| | |
|--|---|
| <p>SC1 - SAFETY CABLE</p> <p>1/16" stainless steel safety cable for added support. Standard kit is 18" and double barrel locks are provided. Approved for California seismic requirements. Rated at 50 lbs.</p> | <p>SC2 - SAFETY CABLE</p> <p>1/16" Stainless steel cable holds door to fixture</p> |
|--|---|

REFRACTOR, GUARD AND LENS OPTIONS

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES, CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.






REFRACTOR OPTIONS

| | | | | | | | | | |
|--|--|--|---|--|---|--|--|---|---|
| DF - DIFFUSE PRISMATIC ACRYLIC REFRACTOR  | PR - CLEAR PRISMATIC ACRYLIC REFRACTOR  | OP - OPAL WHITE ACRYLIC REFRACTOR  | AL - ALUMINUM REFLECTOR  | | | | | | |
| POLY: Polycarbonate Refractor Option Available. Specify As: PR (12", 16", 22") POLY | | | | | | | | | |
| COLOR: Color Refractor Options Available. Specify As: PR (12", 16", 22") (COLOR) | | | | | | | | | |
| GRANITE  | METALIZED  | AMBER  | RED  | GREEN  | BLUE  | PEARL  | PEARL GREEN  | PEARL BLUE  | PEARL PINK  |
















REFRACTOR OPTIONS

We offer traditional Flat Wire Guards (**WAG**), Half-Fixture Wire Guards (**HWG**) and Reflector Shields (**RS**). LED Fixtures typically do not require wireguards.

| | | |
|--|---|---|
| FACE WIRE GUARDS (WAG 12", 16", 22") Guard Covers opening of reflector. May be combined with flat lenses OA , FO , PC , PP . Chrome Plated #14 ga wire.  | HALF WIRE GUARD (HWG12", 16", 22") Covers and protects opening of reflector and exterior. Chrome plated #14 ga wire.  | REFLECTOR SHIELD (RS 12", 16", 22") Reflector Shield used on PR refractor minimizes side light output while allowing up light (30%) Finished to match fixture.  |
|--|---|---|

DIFFUSER OPTIONS

Spectrum offers several lens options for visual comfort, light distribution and interior protection.
2 lens retaining options: **BAND CLAMP: (BC12, BC16, BC22)** and **DOOR: (DR12, DR16, DR22)**

| | | | |
|---|--|---|--|
| CNFR - CONICAL FROSTED LENS (Distributes light horizontally with light etch to diffuse output.)  BC (12", 16", 22") CNFR  DR (12", 16", 22") CNFR | | CN - CONICAL LENS (Distributes light horizontally with clear spread pattern for maximum efficiency.)  BC (12", 16", 22") CN  DR (12", 16", 22") CN | |
| DL - DROP LENS (Drop Prismatic Lens for maximum brightness and widest distribution.)  BC (16", 22") DL  DR (16", 22") DL | | FO - FLAT OPTICAL (Matte White Optical Lens for LED. No LED image for maximum efficiency.)  BC (12", 16", 22") FO  DR (12", 16", 22") FO | |
| PP - PRISMATIC POLYCARBONATE (Classic Prismatic Poly Lens.)  BC (12", 16", 22") PP  DR (12", 16", 22") PP | | PC - CLEAR POLYCARBONATE (Primarily used as safety overlay for FO, PP, OA lens.)  BC (12", 16", 22") PC  DR (12", 16", 22") PP | |
| OA - OPAL ACRYLIC (Matte White Acrylic Lens.)  BC (12", 16", 22") OA  DR (12", 16", 22") OA | | SC2 - SAFETY CABLE (Optional 1/16" Stainless steel cable holds door to fixture.)  | |