







#OF	Н	L	W
MODULES	Α	В	С
1	12.6	12.0	12.6
2	12.6	24.0	12.6
3	12.6	36.0	12.6
4	12.6	48.0	12.6

MODULAR ACCENT LIGHT **CORNER SURFACE MOUNT**

INC SERIES / MULTI-MODULE / 4 x PAR38



CM10-0INC

APPLICATION

CM10 series modular accent light designed for ceiling corner mounting.

FEATURES

Surface mounted modular accent fixture. Fixture available in four sizes with 1-4 modules. Standard front loading lamp bezel accepts up to two lens/louver options. Lamp bezel tilts 30° for aiming.

FINISH

A variety of architectural powdercoat finishes are available.

ELECTRONICS

120V Incandescent standard. 277V step down transformer available (T277). Maximum wattage label (MWL) for low wattage Halogen or LED lamps. Accepts meduim base halogen or LED PAR38 lamps.

CONSTRUCTION

Housing formed #20 gauge galvanized steel, finished to specification.

CODE COMPLIANCE

ARRA Compliant. Non-IC rated. ETL listed for damp locations. Manufactured and tested to UL standards No. 1598.

RECESSED HOUSING SPECIFICATION		TRIM SPECIFICATION		
SERIES	LAMPS	MOUNTING	OPTIONS ¹	FINISHES ³
CM1010INCX1 1 Module CM1020INCX2 2 Modules CM1030INCX3 3 Modules CM1040INCX4	PAR38	SM Surface Mount	LENS HL39 Hex Louver SN39 Snoot 1227 277V to 120V Step Down Transformer LN392 Color Lens OPTIONS MWL(**) Max Wattage Label FS Fusing	MW Matte White GW Gloss White MB Matte Black BZ Bronze PT Platinum CH Charcoal GH Graphite SN Sun Gold OB Oil Rubbed Bronze
4 Modules			raing	AM Anodic Malachite CC Custom Color WF White Flange

EXAMPLE: CM1040INCX4PAR38SM/MW

NOTES:
1 See Product Options Page for Details 2 See Lens Options Page for Details 3 Contact Factory for Special Finishes

Dimensions and values shown are nominal. Spectrum Lighting confinually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.



PROJECT:	TYPE:
CAT. NO.:	