


MULTI BAR MOUNTING BRACKETS .050 5052-H32 ALUMINUM HOUSING (New Construction) FLUSH OR REGRESSED TRIM EARRICATED FROM TRIM/LENS OPTIONS ALUMINUM EXTRUSION





Α	В	С	TRIM	S1		
9.9	5.1	8.5	FT1010	11.0		
9.9	5.1	8.5	RT1010	10.5		

10" SQUARE LENSED

ENDURO SERIES / 4000 LUMENS



SR10SQLEDOA

APPLICATION

10" square recessed LED downlight LED features soffit/area light for optimal performance.

FEATURES

Efficient, powerful LED light source, designed to exceed 50,000 hours of life (L70). Multi-Bar mounting brackets. All LED modules and drivers are replaceable and up-gradeable. New and Retrofit/Remodeler options. Wet location use screws fasteners. (4)

FINISH

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

ELECTRONICS

LED module features high brightness white Nichia LEDs. 3-step MacAdam Ellipses binning and CRI 84 minimum. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Housing constructed of .050 5052-H32 aluminum. Trim fabricated from aluminum extrusion and finished to specification.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE										
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	SYSTEM WATTS							
SR10SQLEDOA10L	SR10SQLEDOA12W	1100	12W							
SR10SQLED0A20L	SR10SQLED0A22W	2200	22W							
SR10SQLED0A30L	SR10SQLEDOA33W	3300	33W							
SR10SQLED0A40L	SR10SQLED0A42W	4000	42W							







RT-Regressed Trim/Lens



Retrofit/Remodeler with Flush Trim

SERIES	L	JMENS ¹		ССТ	DRIVER / VOLTAGE ²			OPTIONS ³ TRIM		FINISH			OPTIONS					
SR10SQLEDOA		1000 Lm	30K	3000K	E_	Electronic Driver	1 12		H27* 27* Solid Bars H12 12* - 24* Expandable Bars H06 6* - 12* Expandable Bars B24 24* C-Channel Bars FS Fusing Integral Emergency Battery CR Corrosion Resistant	FLUSH TRIM	TRIM / FLANGE FINISH		LENS					
	30L	2000 Lm 3000 Lm 4000 Lm						H06 CB24		FT1010 Flush Extruded Aluminum Door		ME PT	MW ⁵ Matte White MB Matte Black PT CC ⁶ Platinum Custom Color TRIM / FLANGE FINISH		Matte White Acrylic Lens 90% Efficient Solite Lens Wet Location			
				3500K 4000K	DS10_	10%, 0-10V	2 27			REGRESSED TRIM	REGRESSED FINISH				Wet Location			
						50K	5000K				RM	Remodeler Housing	RT1010 Regressed Extruded Aluminum Door	MW ⁵ Matte White MB Matte Black PT Platinum Silve	MF	White Flange Matching Flange		

EXAMPLE: SR10SQLEDOA20L30KE1BH27/FT1010MW/F0

1 Nominal Source Lumens 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard Bar Hangers 5 Contact Factory for Special Finishes 6 Standard Finish 7 For use with Non Matte White Trim Finish 8 Standard Lens 9 Trim Secured with 4 Screws



PROJECT: QUANTITY: TYPE:





