

# STQ 16" TRACKLIGHT

# THEATRICAL PRO SERIES / 3000 LUMENS



## STQ16XT

### **APPLICATION**

STQ 16" Photo Style Series tracklight for accent display lighting and decorative lighting application.

### **FEATURES**

Photo Style LED track light evokes the look of traditional theatrical fixtures. Fixture rotates 359° and tilts/locks 45°. Passive cooled Zhaga compliant LED module for future maintenance or upgrade. Quick twist LED optics for field adjustment. Track series available with a variety of surface, pendant and cord/clamp mounting.

### **FINISH**

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

### CONSTRUCTION

Fixtures are fabricated in our factory from 5052-H32 aluminum.

#### **ELECTRONICS**

LED system features Xicato LED module with proprietary phosphor technology that provides consistent, stable color with CCT control of +/- 100K over life of the module. Base CRI is 83 with 2 MacAdam Ellipse binning. High CRI is 98 with 1 MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

### **CODE COMPLIANCE**

BAA Compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL Standards No. 1598/8750.

	WATTAGE / LUMENS DATA								
ĺ	PART NUMBER	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW			
	STQ16XT10L	ST-16LEDXT10L	1000	923	9.1	101			
ĺ	STQ16XT13L	ST-16LEDXT13L	1300	1243	13.0	96			
ĺ	STQ16XT20L	ST-16LEDXT20L	2000	1913	21.7	88			
	STQ16XT30L	N/A	3000	2869	32.6	88			

SERIES	LU	MENS <sup>1</sup>	С	СТ	BE/	AΜ	D	DRIVER / VOLTAGE4		ADAPTOR / MOUNTING		FINISH <sup>10</sup>		ACCESSORIES <sup>12</sup>		
STQ16XT	10L	1000 Lm	83	CRI	XN <sup>3</sup>	10°	<b>E</b> _5	Electronic Driver	1	120V		ADAPTOR	MW11	Matte White	so	Micro Prism
Integral Barn	13L	1300 Lm	27K	2700K	ND	26°	DS10_6	10% 0-10V Dimming	2	277V	TEK100	Global TEK 2 CIR/2 NEUT 120V	MB <sup>11</sup>	Matte Black		Solite™ Lens
Doors	20L	2000 Lm	30K	3000K	MD	48°	DS2W1	ELV MLV 1% Phase			HTEK100	Global TEK 2 CIR/2 NEUT 277V	PT <sup>11</sup>	Platinum Silver	GL	Clear Glass Lens
	30L	3000 Lm	35K	3500K	WD	60°		Dimming, 120V Only			GES66	Global GES 1 CIR/1 NEUT 120V	CC	Custom Color	FG	Frosted Glass Lens
STX16XT			40K	4000K								Global XTSC 3 CIR/1 NEUT 120V,			SK	Skytex™ Lens
No Barn Doors											TP37	0-10V Dimmable			HL	Hex Louver
			98	CRI								MOUNTING				
			27HK	2700K							PC1	Pipe Clamp	<u> </u>			
			30HK	3000K							CP6	6" Straight Cord & Plug		See Page 3 Full Range of		
			35HK	3500K							CP24	24" Straight Cord & Plug		color Options		
			40HK	4000K							CCP6	6" Coil Cord & Plug		(83-90102)		
											CP5	5" Round Surface Mount				
												Canopy (120V/277V)				
											MPT3 <sup>8</sup>	Monopoint Canopy				
											PM(xx)9	Pendant with Track Adaptor,				
												PC1 or CP5				

## EXAMPLE: STQ16XT10L27KNDE1/TEK100/PM36/MW/SO

1 Nominal Source Lumens at Any CCT 2 Nominal Delivered Lumens at 83 CRI at Any CCT With ND, No Lens 3 9mm, 13L Max, All XN Draw More Watts Than Other Optics: See Photometry 4 Contact Factory for Additional Options 5 277V Requires HTEK 277V Track and Adaptor 6 Requires TP3 Adaptor and XTSC PULSE Track System, 120V Only 7 120V 0-10V Only 8 120V Only / GES66 Adaptor 9 Specify Length in Inches 10 See Color Page for More Options/Consult Factory for Special Finishes 11 Standard Finishes 12 Accessory Finish Will Match Fixture



PROJECT:







Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products

# 16" PHOTO STYLE SERIES TRACKLIGHT





### STANDARD FINISHES

Black adaptor standard for all finishes excluding MW which comes with white adaptor.

MW - MATTE WHITE











### **FIXTURE DIMENSIONS**

### BARN DOORS










45° TILT



Α	В	С	D	E		
10.9	4.7	7.0	4.5	5.8		
276.9 mm	119.4 mm	177.8 mm	114.3 mm	147.3 mm		

# **COLOR OPTIONS - POWDER COAT PAINT FINISHES**

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



## STANDARD CORD / STEM / CANOPY FINISHES / TRACK ADAPTER


FIXTURE COLOR	STANDARD CORD COLOR / TRACK ADAPTER	STANDARD CANOPY / STEM COLOR		
Matte White	Matte White	Matte White  Matte Black  Same Color as Fixture  Contact Factory		
Matte Black	Matte Black			
All Others	Matte Black			
Custom Color	Contact Factory			

### **PAINT TIMES**

TIER	COST	AVERAGE PAINT TIME*			
Tier 1 - Standard Finishes	\$	0			
Custom Color	Contact Factory	Contact Factory			

<sup>\*</sup>CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

## **TIER 1 - STANDARD FINISHES**



## **CUSTOM COLOR FINISHES**

CONTACT FACTORY

**CC** Custom Color

