





2' x 2' MODULAR ACCENT LIGHT **GRID CEILING**



INC SERIES / MULTI-MODULE / 2 x PAR38

GC24242XPAR38INC - FLUSH TRIM / NON-IC RATED APPLICATION

GC 2' x 2' Series INC accent light designed for automotive and retail applications where crisp focused light is desired.

FEATURES

Unique fixture designed to convert standard 2' x 2' fixtures into high powered accent light. Fixture modules rotate 359°, lock and tilt to 30° for optimal aiming. Fits seamlessly into 2' x 2' grid ceiling. Front loading lamp bezel accepts up to two lens/louver options. TRIM FINISH

A variety of architectural powdercoat finishes are available.

ELECTRONICS

120V Incandescent standard. 277V step down transformer available (T277). Maximum wattage label (MWL) for low wattage Halogen or LED lamps.

CONSTRUCTION

Housing constructed of #18 ga. galvanized steel to resist corrosion.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL listed for damp locations. Manufactured and tested to UL standards No. 1598.

SERIES	VOLTAGE	OPTIONS ¹		INTERIOR		TRIM		FINISHES⁵	
GC24242XPAR38INC 2 Modules	120V	LENS			White	0,000			Matte White
		SO382	Solite Diffusion		Black	ium			Matte Black
		GL38	HL38 Hex Louver BZI		Platinum				Platinum Silver
		HL38		BZI	Bronze				Bronze
		SN38		CCI	Custom				Charcoal
		LN383			Color				Graphite
		OPTIONS						-	Sun Gold
									Champagne
			Emergency Battery					AN	Anodic Natural
			Fusing					CN	Caramel
		WP(xx)	Whip (Length)					сс	Custom Color
		MWL(**)4	Max Wattage Label						
		T277	277V to 120V Step Down						
			Transformer						

EXAMPLE: GC24242XPAR38INCSO38MWI/FWT2424/2RHPAR38MW

NOTES: 1 See Lens Options Page for Details 2 Standard Lens 3 See Lens Options Page for Details 4 20W, 37W, 50W 5 Contact Factory for Special Finishes 6 Standard Finishes



PROJECT: TYPE:



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.