

4" ROUND FLANGELESS DOWNLIGHT

NON-IC CONSTRUCTION

Spectrum's Infinium 4" recessed round kelvin and color tuning downlight series features a shallow plenum housing for general illumination.

LUMENS AND WATTAGE CHART								
PART NUMBER	SOURCE SYST							
RDZO4LU14L		1400	32					

1 Peak Source Lumens

PROJECT:			fixtures
QUANTITY:	TYF	PE:	
MATTE WHITE			
MATTE BLACK	SEMI-DIFFUSE	PLATINUM SILVER	BRONZE

AVAILABLE HOUSING TYPE



PRODUCT SELECTOR GUIDE

		HOUSING	;			MOUNTING OPTIONS			TRIM	OPTIONS	
SERIES	LUMENS	CCT / K	BEAM	CONTROL / VOLTAGE		BAR HANGERS		TRIM TYPE FINISH LENS TRIM O			TRIM OPTIONS
RDZO4LU	14L	80СМХ		DMXLU1	/		/	RD4NLU			
EXAMPLE											
RDZO4LU	14L	80СМХ	MD	DMXLU1	/	BH27	/	RD4NLU	MW	SO	

	HOUSING								MOUNTING OPTIONS			
SERIES	LL	JMENS ¹	cc	T/K	В	EAM	CONTROL / VOLTAGE		BAR HANGERS			
RDZO4LU	14L	1400 Lm	80CMX	16K-80K	MD MD WD XW	20° 30° 40° 50°	The Hi	DMX Configuration Unit Control Via Blutooth ne Antenna. DMX System ad For Multi-Unit System		120V 277V		27" Solid Bars Standard Bar Hangers 12" - 24" Expandable Bars 24" C-Channel Bars

TRIM OPTIONS							
TRIM TYPE		FINISH	LENS			RIM OPTIONS	
RD4NLU	MW MB SG PT CC*	Semi-Diffuse Platinum Silver	SO	Micro Prism Solite™ Lens	GS	Gasket Is Supplied with "W" Option	
		ge (x) for Full Range of or Options (83-90174)					

- Kelvin (16K-80K) and color (RGBW) tuning fixture.
- True saturated greens, blues and reds.
- Controlable with DMX or Bluetooth controls.
- Peak of 1400 source lumens.
- Smooth light distribution for general illumination.
- · Shallow plenum construction.
- L70 at >60,000 Hours at 70% lumens maintenance.
- 5 year warranty on fixture and electronics.
- Sustainable fixture.
- Dry/damp or wet location rated.
- Ease of maintenance.
- Posi-lock trim retention torsion springs.












HOUSING DIMENSIONS

RDZO4LU - NEW CONSTRUCTION / 14L MAX

Non-IC rated, thermally protected frame-in kit for new construction.



TRIM DATA

RD4FLU - DOWNLIGHT





FEATURES

APPLICATIONS

4" Round LU downlight with flangeless trim platform with Tunable color (HUE) system. System can be programmed for scenes or set for manual control. Adjusts to over 300,000 colors as well as 1650K-8000K white light.

FEATURES

Two-stage optical system for smooth light distribution and focus control. Quick change LED module with interchangeable optics for job site adjustment and fixture maintenance. Shallow plenum design. Tool-less driver and j-box access. Posi-lock trim retention torsion springs. Integral 5/8" (.625) collar, works in ceiling up to 1" Deep.

FINISH

Variety of powdercoat and anodized finishes available. Matte white flange is standard.

ELECTRONICS

LED system features LED module with proprietary Tunable color (HUE) technology that provides consistent, stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 90 with <2 MacAdam Ellipse binning. Variety of dimming controls (by Others). The Hive Antenna is the main control app., and is available for both Apple and Android devices.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Flangeless one piece trim high purity aluminum and finished to specification.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.





SPUN FLANGELESS TRIM FINISH OPTIONS - RECESSED ROUND





PAINT TIMES

TIER	COST	PAINT TIME*		
Tier 1 - Standard Finishes	\$	0		
Tier 2 - Typical Finishes	\$	00		
Tier 3 - Anodic Finishes	\$\$	00		
Tier 4 - Alzak Finishes	\$\$\$	000		
Custom Color	Contact Factory	Contact Factory		

POWDER COAT PAINT FINISHES

TIER 1

MW	MB	PT
Matte White	Matte Black	Platinum Silver



SG* Semi-Diffuse



ANODIZED ALZAK FINISHES

TIER 4

CL	HZ	WE	GO	PW
Bright Clear	Haze Full Diffuse	Rose Gold	Gold Alzak Semi-Diffuse	Pewter Semi-Diffuse





AMB***





^{*}CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES