




6" SQUARE WALL WASH FX SERIES / 4000 LUMENS MAX



A	B	C	D	S1	S2
5.5 139.7 mm	.625 15.9 mm	14.2 360.7 mm	7.9 200.7 mm	5.8 147.3 mm	7.5 190.5 mm

SGW6SQLEDFX - TRIM FLANGE / NON-IC RATED

APPLICATIONS

FX series 6" square recessed wall wash designed for general wall washing with smooth light distribution.

FEATURES

Shallow plenum construction. Auto dim thermal protector for long term reliability. Zhaga international standard LED module for ease of maintenance and future replacement. Tool-less LED module, driver, and J-Box access. Multi-Bar mounting brackets, fit a variety of mounting bars. Posi-lock trim retention torsion springs. Integral 5/8" (.625) collar, works in ceiling up to 1." Deep. BH27 Standard mounting bars included. Intended for Non-IC new construction.

FINISH

Variety of powdercoat finishes available.
Matte white flange is standard.

ELECTRONICS

LED system features high efficacy Philips LEDs. Standard CRI is >80. Drivers are overload and short circuit protected as well as thermally regulated. Sound rating A. L70 at >60,000 hours.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-Flanged one piece trim die-cast high purity aluminum and finished to specification. Passive machined aluminum heatsink.

CODE COMPLIANCE

Energy Star pending and BAA Compliant. Non-IC New Construction only. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location listed trim. LM79/LM80 data available. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE / LUMENS DATA		
PART NUMBER	SOURCE LUMENS ¹	SYSTEM WATTS
SGW6SQLEDFX10L	1000	9
SGW6SQLEDFX15L	1500	13
SGW6SQLEDFX20L	2000	17
SGW6SQLEDFX30L	3000	25
SGW6SQLEDFX40L	4000	35

SERIES	LUMENS ¹	CCT	DRIVER / VOLTAGE	OPTIONS	TRIM	FINISH	TRIM OPTIONS
SGW6SQLEDFX	10L 1000 Lm	27K 2700K	DX 1%, 0-10V, 120V/277V	BH27 ² 27" Solid Bars	CA0396FX	MW Matte White	WF White Flange
	15L 1500 Lm	30K 3000K		H12 12" - 24" Expandable Bars		MB Matte Black	MF ⁶ Matching Flange
	20L 2000 Lm	35K 3500K		H06 6" - 12" Expandable Bars		PT Platinum Silver	SK ⁷ Skytex™ Lens
	30L 3000 Lm	40K 4000K		CB24 24" C-Channel Bars		CC ⁵ Custom Color	SKW Skytex™ Lens
	40L 4000 Lm			EM Integral Emergency Battery			SKW Wet Location
			EMRM ³ Remote Emergency Battery Pack				
			FS Fusing				
			CR Corrosion Resistant				
			PR ⁴ Deep Ceiling Extension				

EXAMPLE: SGW6SQLEDFX20L30KDX/BH27/CA0396FXPTMFSK

NOTES:
1 Nominal Source Lumens at 35K 2 Standard Bar Hangers 3 Installer Responsible for EM Access 4 Contact Factory 5 Contact Factory for Special Finishes 6 Flange Same Color as Inside of Trim 7 Standard Lens



PROJECT: _____
TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.