



# SMALL OPEN REFLECTOR

## DAMP / WET LOCATION

### CLASSIC SHAPES

PROJECT: \_\_\_\_\_

QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



OR1514GV  
MB - Matte Black



OR1514GV  
PL - Purple



OR1514GV  
MW - Matte White



OR1514GV  
SF - Sea Foam

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>2</sup>	ACCESSORIES <sup>5</sup>	MOUNTING <sup>8</sup>	INTERIOR <sup>12</sup>	FINISH <sup>12</sup>	WET KIT		
OR1514GV	15L 1500 Lm 27L 2700 Lm	80 CRI	<b>EX</b> Electronic Driver, 120V/277V ELV/MLV, 120V <b>DS2W1</b> 1%, 0-10V, 120V/277V <b>DO10X<sup>3</sup></b> Lutron® 2-Wire Forward Phase (MLV), 120V <b>DLTE1<sup>4</sup></b> 1%, Lutron® EcoSystem®, Fades to Black, 120V/277V <b>DL3EX<sup>4</sup></b>	ENCLOSURES		WALL MOUNT		<b>MW<sup>13</sup></b> Matte White Custom Color <b>CCI</b> Fixture Color Interior <b>FCI</b> See Page 5 for Full Range of Color Options (83-90083)	<b>WLKA</b> Wet Location Kit	
		27K 2700K 30K 3000K 35K 3500K 40K 4000K		<b>TF1<sup>6</sup></b> 3" Frosted Dome <b>MF1</b> 3" Frosted Mini <b>FJ1</b> 3" Frosted Tall	<b>CP104</b> Small Driver Canopy w/ Knockouts <b>CP104KO</b> Small Driver Canopy w/ Knockouts <b>CP106</b> Large Driver Canopy <b>CP6/RMD</b> Remote Mount Driver <b>SP90<sup>9</sup></b> Straight Arm <b>PA<sup>9</sup></b> Mounting Arm Style	<b>MW<sup>13</sup></b> Matte White <b>MB<sup>13</sup></b> Matte Black <b>PT<sup>13</sup></b> Platinum Silver <b>CC</b> Custom Color				
		90 CRI		DOORS & LENSES <sup>7</sup>		CEILING MOUNT				See Page 5 for Full Range of Color Options (83-90083)
		27HK 2700K 30HK 3000K 35HK 3500K 40HK 4000K		<b>DR</b> (See 2 <sup>nd</sup> Page for Ordering Details)	<b>RDC5</b> Small Driver Canopy <b>CP13</b> Large Driver Canopy <b>HM<sup>10</sup></b> Hang Straight <b>AT<sup>10</sup></b> Hang Straight All Thread <b>PM<sup>10</sup></b> Rigid Pendant Mount <b>CD<sup>10</sup></b> Cord / Cable Mount <b>CM<sup>10</sup></b> Cord Mount <b>EMCR<sup>11</sup></b> 10W Large Driver Canopy EM <b>EMRM</b> 7W Remote EM <b>EMEN</b> 7W Remote with Enclosure	See Page 5 for Full Range of Color Options (83-90083)				

EXAMPLE: OR1514GV15L30KEXTF1/RDC5CD36MWIMW

**NOTES:**

- 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Available with CP106/RDC5/CP13 Only 4 Available with CP106/CP13 Only
- 5 Enclosure or Door & Lens Required - Choose One Option 6 Standard Enclosure 7 Requires TF1 Enclosure 8 See Mounting Page for Details on Components and Finishes
- 9 See Mounting Page for Available Arm Options 10 Specify Length in Inches; See Mounting Page for Available Lengths 11 EMCR Replaces RDC5 or CP13
- 12 See Color Page for More Options/Consult Factory for Special Finishes 13 Standard Finishes





# SMALL OPEN REFLECTOR


## DAMP / WET LOCATION

### CLASSIC SHAPES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
OR1514GV15L	1500	965	10	97
OR1514GV27L	2700	1683	18	94

<sup>1</sup> Nominal Source Lumens at 35K    <sup>2</sup> Nominal Delivered Lumens at 35K

## HOUSING DIMENSIONS



A	B
14.5	14.8
368.3 mm	375.9 mm

## APPLICATION

The Open Reflector RLM offers 95% downlight and 5% up-light.

## FEATURES

Spectrum Lighting's RLM Classics are inspired by vintage lighting fixtures redesigned with modern LED light sources and materials. The wide range of options for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. LED module and driver are serviceable for future replacement.

## FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Interior is Matte White unless specified. Custom Color interior finish available.

## ELECTRONICS

GV LED system features high brightness white Samsung LED's, 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.

## CONSTRUCTION

Fixture shades are spun in our factory from high purity aluminum 0.080 for the reflector and 0.060 for the top cap. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe and may be field cut.

## CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Wet Location Option. Manufactured and tested to UL standards No. 1598/8750.

## ENCLOSURES



## DOORS    LENSES

DR14A- 14" Ø    FO- WHITE OPTICAL ACRYLIC



OR1514GV SHOWN WITH DR14AFO

## WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

PA  
MOUNTING ARM STYLE



OR1514GV SHOWN WITH CP104PA23

## CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM  
HANG STRAIGHT / ALL THREAD / PENDANT



OR1514GV SHOWN WITH RDC5PM

CD  
CORD / CABLE MOUNT



OR1514GV SHOWN WITH RDC5CD

CM  
CORD MOUNT



OR1514GV SHOWN WITH RDC5CM




# SMALL OPEN REFLECTOR

## DAMP / WET LOCATION

### CLASSIC SHAPES / PHOTOMETRIC DATA

OR1514GV-27L-35K-EX-TF1-MWI

#### CANDLEPOWER CURVE



Delivered Lumens: 1,683  
 Luminaire Watts: 18  
 LER: 93.50

#### INTENSITY

Intensity (cd)	Beam Angle (°)
0.00	0.00°
1.251	0.00°
1.187	5.00°
1.069	10.00°
966	15.00°
881	20.00°
687	30.00°
233	40.00°
150	50.00°
148	60.00°
123	70.00°
84	80.00°
45	90.00°

CP at 0deg (Nadir): 1,251  
 CRI: 85+

#### ZONAL LUMENS

Beam Angle Range (°)	Zonal Lumens	% of Total
0° - 10°	112	7%
0° - 20°	386	23%
0° - 30°	753	45%
0° - 40°	1,027	61%
0° - 60°	1,290	77%
0° - 80°	1,530	91%
0° - 90°	1,594	95%
Total	1,683	100%

Beam Angle: 63.06  
 Spacing Ratio: 0.89

#### SINGLE UNIT: PERFORMANCE

Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge
5.50'	41 fc	6.9'	20 fc
6.50'	30 fc	8.2'	15 fc
7.50'	22 fc	9.5'	11 fc
8.50'	17 fc	10.7'	9 fc
10.00'	13 fc	12.6'	6 fc
12.00'	9 fc	15.1'	4 fc
14.00'	6 fc	17.6'	3 fc
16.00'	5 fc	20.2'	2 fc

#### MULTIPLE UNITS: PERFORMANCE

Ceiling Height	Fixture Spacing	RCR 2		RCR 4	
		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.
8'	6' *	45	0.53	65	0.94
12'	8' **	27	0.32	14	0.20
16'	10' ***	17	0.20	14	0.20
Delivered Illuminance Rating: (DIR)		85 FC per W/Sq. Ft.		69 FC per W/Sq. Ft.	
2' Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00' - RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50' * Average Footcandles at 2.5' Above Floor ** Exceeds spacing criteria by 93% *** Exceeds spacing criteria by 20%					

Lamp Multiplier: 15L x 0.573  
 CCT Multiplier: 27K x 0.971, 30K x 0.985, 40K x 1.03




# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




## WALL MOUNTING


**CP104 - SMALL DRIVER CANOPY (STANDARD)**  
MAY BE USED AS SPLICE BOX FOR DIRECT FEED  
NOT AVAILABLE W/ PA16 & PA16F




**CP106 - LARGE DRIVER CANOPY**  
MAY BE USED AS SPLICE BOX FOR DIRECT FEED



**CP6/RMD - REMOTE MOUNT DRIVER**  
MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX




CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.




## CEILING MOUNTING


**RDC5 - SMALL DRIVER CANOPY (STANDARD)**  
MOUNTS TO 4" OCTO J-BOX



**CP13 - LARGE DRIVER CANOPY**




**HM\***  
HANG STRAIGHT  
45° SWIVEL 5/8" OD STEM - 3/8" IP




ORDER: HM (Length)  
SPECIFY LENGTH:  
HM3 - 3" HM24 - 24"  
HM6 - 6" HM36 - 36"  
HM12 - 12" HM48 - 48"  
HM18 - 18" HM72 - 72"  
HMLC(XX)  
Custom Length  
(Specify in Inches)

**PM\***  
RIGID PENDANT MOUNT  
RIGID 5/8" OD STEM - 3/8" IP



ORDER: PM (Length)  
SPECIFY LENGTH:  
PM3 - 3" PM24 - 24"  
PM6 - 6" PM36 - 36"  
PM12 - 12" PM48 - 48"  
PM18 - 18" PM72 - 72"  
PMLC(XX)  
Custom Length  
(Specify in Inches)

**AT\*\***  
HANG STRAIGHT ALL THREAD  
45° SWIVEL 5/8" OD STEM - 1/4" IP



ORDER: AT (Length)  
SPECIFY LENGTH:  
AT12 - 12"  
AT24 - 24"  
AT36 - 36"  
AT48 - 48"  
AT60 - 60"  
AT72 - 72"  
FIELD CUT THREADED PIPE TO LENGTH NEEDED. CUT PIPE COVER IS SHORTER THAN THREADED PIPE. SUPPLY COVER OVER THREADED PIPE.

**CD**  
CORD / CABLE MOUNT  
SJ CORD WITH 1/16 SS CABLE



ORDER: CD (Length)  
SPECIFY LENGTH:  
CD36 - 36"  
CD72 - 72"  
CD144 - 144"  
CDLC(XX)  
Custom Length  
(Specify in Inches)

**CM**  
CORD MOUNT  
SJ CORD WITH STRAIN RELIEF




ORDER: CM (Length)  
SPECIFY LENGTH:  
CM36 - 36"  
CM72 - 72"  
CM144 - 144"  
CMLC(XX)  
Custom Length  
(Specify in Inches)

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. \*\*ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT


## EMERGENCY BATTERY OPTIONS

**EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY**




## REMOTE EMERGENCY BATTERY OPTIONS

**EMRM\* - 7W REMOTE EMERGENCY BATTERY (50' MAX)**



**EMEN\* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)**



\*OTHER EM BATTERY SIZES AVAILABLE. CONTACT FACTORY.



# COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.  
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



## STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

## PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	⓪
Tier 2 - Typical Finishes	\$\$	⓪⓪
Tier 3 - Special Metal Finishes	\$\$\$	⓪⓪⓪
Custom Color	Contact Factory	Contact Factory

\*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES


## TIER 1 - STANDARD FINISHES



## TIER 2 - TYPICAL FINISHES



## TIER 3 - SPECIAL METAL FINISHES



## CUSTOM COLOR FINISHES

CONTACT FACTORY

**CC**  
Custom Color



\*UNAVAILABLE FOR WET LOCATION

