


RDC5 ROUND SURFACE MOUNT DRIVER CANOPY





AMBIENT INDIRECT SCONCE

XL SERIES / 2000 LUMEN MAX LED



ID406LEDXL - RDC5

APPLICATION

Ambient Series Sconce for indirect lighting illumination. Modern replacement for classic halogen fixture.

FEATURES

Wedge profile and clean detailing blend easily into interior design. Optics produce forward throw indirect output. Illuminates a wide area with smooth, hot-spot free illumination. Top lens available, in clear tempered glass or Solite™ Lens. Designed for surface mounting to octagonal J box.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 80 with 1x2 MacAdam Ellipses binning.

CONSTRUCTION

Fixture is die cast aluminum with stainless steel hardware. Recessed in wall housing is 20ga. galvanized steel to resist corrosion.

CODE COMPLIANCE

BAA Compliant. UL listed. Damp location only. Manufactured and tested to UL standards No. 1598/8750.

| WATTAGE / LUMENS DATA | | | | | | | | | |
|-----------------------|-------------------------------|---------------------|-----------------|-----|--|--|--|--|--|
| PART NUMBER | SOURCE LUMENS ¹ | DELIVERED LUMENS | SYSTEM WATTS | LPW | | | | | |
| ID406LEDXL16L | 1600 | 1405 | 21.0 | 67 | | | | | |
| ID406LEDXL20L | 2000 | 1694 | 27.7 | 61 | | | | | |

| SERIES | L | ED ¹ | С | CT | D | RIVER / DIMMING ³ | | LENS | | MOUNTING | | FINISH⁵ |
|------------|-----|-----------------|-----|-------|-------|------------------------------|-----------------|---------------------|------|----------------------|-----------------|-----------------|
| ID406LEDXL | 16L | 1600 Lm | 27K | 2700K | EX | Electronic Driver, 120V/277V | GL ⁴ | Clear Glass Lens | RDC5 | Round Surface Driver | MW ⁶ | Matte White |
| | 20L | 2000 Lm | 30K | 3000K | DS10X | 10%, 0-10V, 120V/277V | SO | Micro Prism Solite™ | | Canopy | MB ⁶ | Matte Black |
| | | | 35K | 3500K | DS2W1 | 1%, ELV/MLV, 120V, Dims to 0 | | Lens | | | PT⁰ | Platinum Silver |
| | | | | | DO10X | 1%, 0-10V, 120V/277V | | | | | cc | Custom Color |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

EXAMPLE: ID406LEDXL20L35KDS2W1GLRDC5MW

NOTES: 1 Nominal Source Lumens at 3500K 2 Nominal Delivered Lumens at 80 CRI at Any CCT, No Lens 3 Contact Factory for Additional Options 4 Glass is Standard 5 Contact Factory for Special Finishes 6 Standard Finishes





SS/≜

Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products. the performa



PROJECT: TYPE: CAT. NO.:

WWW.SPECLIGHT.COM • 994 JEFFERSON STREET, FALL RIVER, MA 02721 • 508.678.2303 FAX 508.678.2260